



Our class winner. Sophisticated, low-noise technology. Large collecting bin in a dustproof cabinet. Comfortable operation. Auto reverse when overloaded.

- i-control®** Absolute transparency of the work flow
- EcoLogic** Energy efficiency
- DLS** Dynamic Load Sensor - controlled performance

- ✓ Mounted on rollers for flexible use
- ✓ On/off control via light barrier
- ✓ Material: shock resistant plastic, wood

### Technical data

Cutting size paper (mm)	0,8 x 4,5 mm
Amount of paper:	10+ users
Security level DIN 32757-1	6
Shredding capacity 70 g/m <sup>2</sup> :	8-10 sheets
Cutting speed 70 g/m <sup>2</sup> (m/Sec.):	0,23 m/sec.
Cutting speed 70 g/m <sup>2</sup> (sheets/Min.):	465 sheets/min.
Shredding capacity 80 g/m <sup>2</sup> :	7-9 sheets
Cutting speed 80 g/m <sup>2</sup> (m/Sec.):	0,23 m/sec.
Cutting speed 80 g/m <sup>2</sup> (sheets/Min.):	418 sheets/min.
Working width (mm):	405 mm
DIN paper size:	A3
Catchbasket volume (l):	175 l
Catchbasket volume (sheets):	8320 sheets
Power consumption (kW):	1,9 kW
Supply voltage (Volt):	230 Volt
Noise level:	52 db(A)
Weight gross (kg):	119 kg
Weight net (kg):	90 kg
Warranty on machine (years):	2 years
Warranty on the fracture of cutting cylinders:	2 years
Width (cm):	66 cm
Depth (cm):	56 cm
Height (cm):	105 cm
Type of packaging:	Box on pallet
Packaging dimensions (L/W/H):	76/88/120 cm
Packing unit:	1

## Accessories

---

- 999 52 PE bags
- 858 29 Receptacle
- 880 35 Shredder oil for cross-cut shredder
- 801 80 Shredder oil for cross-cut shredders (re-fill)

---

[www.intimus.eu/index.php?intimus\\_pro-175\\_CC6\\_en](http://www.intimus.eu/index.php?intimus_pro-175_CC6_en)