

RETRACTABLE FOAM NOZZLES

372E-Series Constant Gallonage Foam Nozzle

- Combination pattern nozzle with versatile multiple flow settings
- Ability to instantly aspirate foam by sliding inbuilt sleeve forward
- No foam aeration tube required for aspiration foam
- Stainless steel spinning teeth for superior fog pattern
- 60, 95 or 125 GPM (230, 360 or 475 LPM)
- Standard operating pressure at 100 psi (7 bar), optional 85 psi (6 bar) or 75 psi (5 bar)
- Optional 2-1/2" inlet size

372E **1-1/2" Selectable Gallonage Foam Nozzle**

372E-TO **1-1/2" Selectable Gallonage Foam Nozzle Tip Only**

372E-BC **1-1/2" Selectable Gallonage Foam Nozzle**

- Industrial nozzle
- Brass construction

372E-BCTO **1-1/2" Selectable Gallonage Foam Nozzle Tip Only**

- Brass construction



Style 372E



Style 372E-TO



Style 372E-BC



Style 372E-BCTO

Style	Inlet Size	Length	Weight Lbs(kg)	Flow Settings	
				GPM	LPM
372E	1-1/2"(38mm)	8.3" to 11.4" (210mm-290mm)	4.4 (2kg)	60, 95 or 125	230, 360 or 475
372E-TO	1-1/2"(38mm)	5.5" to 8.8" (140mm-225mm)	2.9 (1.3kg)	60, 95 or 125	230, 360 or 475
372E-BC	1-1/2"(38mm)	8.3" to 11.4" (210mm-290mm)	8.8 (4kg)	60, 95 or 125	230, 360 or 475
372E-BCTO	1-1/2"(38mm)	5.5" to 8.8" (140mm-225mm)	5.5 (2.5kg)	60, 95 or 125	230, 360 or 475

