

ADJUSTABLE FLOW-BAFFLE MONITOR NOZZLE

- Spring loaded baffle enables flow rate selection.
- Combination of straight stream and variable fog patterns.
- Fog pattern is wide, dense and fully adjustable.
- Low maintenance, high quality components.
- Varying flow settings with an easy turn of the baffle.
- Available in lightweight alloy or brass construction.



Style 818
Style 819
Style 820



Style 818-BC
Style 819-BC
Style 820-BC

Specification

Style	Material	Inlet Size	Flow @ 100psi (7 bar)		Teeth	Length	Weight Lbs (kg)
			GPM	LPM			
818	Alloy	1-1/2" or 2-1/2" (38 or 65 mm)	15, 30, 45	56, 115, 170	Spinning	5.5" (140mm)	2.6 (1.2)
818-BC	Brass	1-1/2" or 2-1/2" (38 or 65 mm)	15, 30, 45	56, 115, 170	Spinning	5.5" (140mm)	7.3 (3.3)
819	Alloy	1-1/2" or 2-1/2" (38 or 65 mm)	60, 95, 125	230, 360, 475	Spinning	5.5" (140mm)	2.6 (1.2)
819-BC	Brass	1-1/2" or 2-1/2" (38 or 65 mm)	60, 95, 125	230, 360, 475	Spinning	5.5" (140mm)	7.3 (3.3)
820	Alloy	1-1/2" or 2-1/2" (38 or 65 mm)	200, 250, 350	750, 950, 1325	Spinning	5.5" (140mm)	2.6 (1.2)
820-BC	Brass	1-1/2" or 2-1/2" (38 or 65 mm)	200, 250, 350	750, 950, 1325	Spinning	5.5" (140mm)	7.3 (3.3)