

# AS-IS BRAND

WOOD PANELS BY INSTONE

## PRODUCT DATA SHEET

### Product Description

Every piece of AS-IS BRAND Wood Walls is handcrafted to capture the look and feel of naturally distressed wood or soften a space with gentle wood tones. All wood has been carefully chosen from sustainable harvested sources.

All wood is then carefully milled to exact measurements to ensure a precise board for fast and easy installation. AS-IS is proud to use materials, manufacturing, and packaging that have positive social and environmental impacts. Everything is done in North America, but our positive impact is global. Visit [as-isbrand.com/trees](http://as-isbrand.com/trees).

### Materials

#### KILN-DRIED SUGAR PINE WOOD WITH A PAINT FINISH

All boards come standard with Flamex PF applied at a rate of one gallon per 125 square feet to meet NFI's requirement, and to achieve 'Class A' Fire Protection and Flame spread.

**FLAMESPREAD: 25 | SMOKE DEVELOPED: 95**

### Limitations

AS-IS BRAND Wood Walls do not add to the structural load bearing capacity of the substrate to which it is being applied. All products have been designed for wall and ceiling installation only and should not be applied anywhere where they will be walked or sat on.

### Product Dimensions

| LENGTH    | HEIGHT | THICKNESS | COVERAGE/BOX |
|-----------|--------|-----------|--------------|
| 12" - 48" | 5"     | ¼"        | 20 sq. ft.   |

Board lengths will vary, but will total 48".  
Other dimensions available upon request.

### Applications

Interior only: facades, walls, ceilings, furniture, doors, cabinets and other non-load bearing surfaces.

### Advantages



Insect Free



Non-Toxic



Class A



Install Friendly



Kiln-Dried



Responsibly Sustainable



100% Real Wood



Made in North America

### Collections



**The ISH Collection**



**The SMOOTH Collection**

### Available Colours



WHITE-ISH



GREY-ISH



UMBER-ISH




RED-ISH




RAW-ISH



BROWN-ISH



BLUE-ISH



BLACK-ISH

### Box and Pallet Dimensions

| BOX LENGTH    | BOX HEIGHT    | BOX THICKNESS    | BOX WEIGHT          |
|---------------|---------------|------------------|---------------------|
| 49"           | 5½"           | 3½"              | 12 lbs.             |
| PALLET LENGTH | PALLET HEIGHT | PALLET THICKNESS | PALLET WEIGHT       |
| 60"           | 50"           | 48"              | 800 lbs. (60 boxes) |

### AS-IS Properties

| FEATURE  | UNIT    | VALUE | STANDARD |
|--|---------|-------|----------|
| FIRE RESISTANCE                                | Class A |       |          |
| VOC CONTENT                                    | 3g/100  | 1, 5  | EN 317   |
| MOISTURE CONTENT AT DISPATCH FROM MANUFACTURER | <8%     | 9 -12 | EN 322   |
| IMPACT RESISTANCE                              | High    | 4500  | EN 310   |
| FLEXURAL STRENGTH                              | Medium  | 0, 50 | EN 319   |

### Recommended Finishing Products

The following products are recommended with AS-IS products. See install instructions for details on how/when to use.

- Polyurethane Construction Adhesive (DO NOT USE water/latex-based adhesive)
  - We recommend Titebond Titegrab or Gorilla Glue
  - Approx. (1) 10.3oz tube / box. (using ¼" bead over ¾ of the length of the board)
- 1" Air-Powered Nail (Brad Nail) if air (pneumatic) nail gun is being used
- 1" Finishing Nail if hammer is being used
- Heavy-duty 2-sided tape for a temporary installation

### Care and Cleaning

Because of the high-grade coating formulation used, AS-IS BRAND boards are easily cleaned with a duster or a slightly-damped wash cloth. Do not use anything rough, chemicals, or anything acidic to clean. This could damage the surface and the wood. Some tougher debris/stains can be eliminated with water and a light brushing with a soft bristle brush. Always trial a small area first to ensure the procedure is working, and to check for color fastness.

Sealers are not necessary on AS-IS BRAND products, unless the boards are being utilized where not recommended. If a sealer is desired for your particular use, make sure it is compatible with untreated wood and water-based paints. Sealers may darken the color of the wood, and usually add different degrees of shine as well.

### Warranty

#### LIMITED WARRANTY TO ORIGINAL PURCHASER ONLY

Subject to the terms, conditions, and limitations stated in our full warranty, InStone provides this limited warranty only to the person or entity that originally purchased (the "Original Purchaser") any AS-IS BRAND Wood Wall boards (the "Product") from InStone.

InStone warrants that the Product will not have excessive peeling, flaking, blistering, or corrosion solely as a result of defects in materials or workmanship (the "Warranty") for a period of five (5) years full warranty from the original date of purchase (the "Warranty Period"). Some peeling, flaking, or blistering may occur if the product is installed in a fashion or environment not recommended by InStone.