

# hour wall

modern in minutes

## urbanCONCRETE SPEC DATA SHEET



### SECTION A - General Product Information

**Product Name:** Hourwall urbanCONCRETE

**Suppliers:** **CANADA**  
Products  
[www.instoneproducts.ca](http://www.instoneproducts.ca)

**US**  
Border Products  
[www.borderproducts.net](http://www.borderproducts.net)

#### Product Description:

Every piece of Hourwall's product line has been precisely cast off of real wood, brick, and concrete. All pieces used are carefully chosen for their rich texture, shape, and size. Then colors are chosen and added into the process to provide the realistic and rich details. This technology is combined into a panel system, making it quick and easy to install. The high density polyurethane used to create our panels allows for a very lightweight panel with the look and feel of the real thing. Hourwall products are made of 98% closed-cell structural polyurethane and a titanium oxide finish. We have no testing data to support use in an underwater or heavy moisture environment.

#### Limitations:

Hourwall products do not add to the structural load bearing capacity of the substrate to which it is being applied. All products have been designed for wall installation only, and should not be applied anywhere that they will be walked or sat on.

### SECTION B – Product Specifications

Product	Dimensions			Wt. (lbs)	Box		Pallet	
	Length (in)	Height (in)	Thickness (in)		Items/ box	Total lbs	Boxes/pallet	Total lbs
24x48 urbanCONCRETE	48	24	1	8	2	16	50	1650
48x48 urbanCONCRETE	48	48	1	16	2	32	25	1650
STONE FINISH	10.3 oz	-	-	1.1	12	13	-	-
PAINT KIT (box)	5.5	2	5.5	-	4	1	-	-

**COVERAGE**

Product	Approx. sq.ft / PIECE	Approx. sq.ft / BOX	Approx. sq.ft / PALLET
<b>24x48 urbanCONCRETE</b>	8	16	800 sq.ft (50 boxes)
<b>48x48 urbanCONCRETE</b>	16	32	800 sq.ft (25 boxes)
<b>classicBRICK</b>	7.42	14.84	742 sq.ft (50 boxes)
<b>barnWOOD</b>	2	24	1152 sq.ft (48 boxes)
<b>STONE FINISH</b>	-	Approx. 100 sq.ft / tube	-
<b>PAINT</b>	-	Approx. 300 sq.ft / box	-

**STANDARD BOX and PALLET Dimensions****24x48 urbanCONCRETE (20 lbs.)**

Box Dimensions = 50" x 26" x 3"  
Pallet Dimension = 50" x 48" x 95"  
Pallet = 50 boxes

**48x48 urbanCONCRETE (40 lbs.)**

Box Dimensions = 50" x 50" x 3"  
Pallet Dimension = 50" x 48" x 95"  
Pallet = 25 boxes

**Stone Finish**

Box Dimensions = 12" x 8" x 6"

**Paint Kits (Touch Up)**

Box Dimensions = 2" x 5.5" x 5.5"

**SECTION C – Technical Data****STANDARD PRODUCT**

ASTM E-84 / UL 723	Flame Spread Average: 765	Smoke Density Average: 350 - 450
ASTM D1929	Self-Ignition Temperature	540 deg. C (1004 deg. F)
	Water Resistance	Showed no visual sign of degradation
ASTM G26	Weatherability	Showed no visual sign of degradation
ASTM C518	Thermal Transmission properties	R 3.6 or greater
	Freeze / Thaw	Showed no visual sign of degradation

\* Check local building codes to see if a Class A (or better) material is required.

**\*PROTECH CLASS A / CLASS I PRODUCT**

(Special Order product. Will have a surcharge)

ASTM E-84 / UL 723	Flame Spread Average: 20	Smoke Density Average: 350 - 450
ASTM D1622	Molded Core Density	14pcf
ASTM D1621	Compressive Strength	11 to rise, 310 psi
ASTM D790	Flexural Strength	11 to rise, 700 psi
ASTM D2240	Shore D Hardness	37

\* Check local building codes to see if a Class A (or better) material is required.

**SECTION D – Installation**

Installation Instructions are available at [www.qualitystoneproducts.com](http://www.qualitystoneproducts.com)

**SECTION E – Warranty**

Warranty information is available at [www.qualitystoneproducts.com](http://www.qualitystoneproducts.com)