


Article	H/h, inch	Weight, (total), lb	H/h, mm	Weight, (total), kg
07507155/310	12,2	125,2	310	56,9
07507155/305	12,0	123,9	305	56,3
07507155/300	11,8	122,5	300	55,7
07507155/295	11,6	121,2	295	55,1
07507155/290	11,4	119,8	290	54,5
07507155/285	11,2	118,5	285	53,9
07507155/280	11,0	117,1	280	53,2
07507155/275	10,8	115,7	275	52,6
07507155/270	10,6	114,4	270	52,0
07507155/265	10,4	113,0	265	51,4
07507155/260	10,2	111,7	260	50,8
07507155/255	10,0	116,6	255	53,0
07507155/250	9,8	115,3	250	52,4
07507155/245	9,6	114,0	245	51,8
07507155/240	9,4	112,6	240	51,2
07507155/235	9,3	111,3	235	50,6
07507155/230	9,1	110,0	230	50,0
07507155/225	8,9	108,7	225	49,4
07507155/220	8,7	107,4	220	48,8
07507155/215	8,5	106,0	215	48,2
07507155/210	8,3	104,7	210	47,6

Article	H/h, inch	Weight, (total), lb	H/h, mm	Weight, (total), kg
07507155/310-305	12,2/12,0	124,7	310/305	56,7
07507155/305-300	12,0/11,8	123,2	305/300	56,0
07507155/300-295	11,8/11,6	121,9	300/295	55,4
07507155/295-290	11,6/11,4	120,6	295/290	54,8
07507155/290-285	11,4/11,2	119,2	290/285	54,2
07507155/285-280	11,2/11,0	117,9	285/280	53,6
07507155/280-275	11,0/10,8	116,6	280/275	53,0
07507155/275-270	10,8/10,6	115,3	275/270	52,4
07507155/270-265	10,6/10,4	114,0	270/265	51,8
07507155/265-260	10,4/10,2	112,6	265/260	51,2
07507155/260-255	10,2/10,0	115,9	260/255	52,7
07507155/255-250	10,0/9,8	114,6	255/250	52,1
07507155/250-245	9,8/9,6	113,3	250/245	51,5
07507155/245-240	9,6/9,4	112,0	245/240	50,9
07507155/240-235	9,4/9,3	110,7	240/235	50,3
07507155/235-230	9,3/9,1	109,3	235/230	49,7
07507155/230-225	9,1/8,9	108,0	230/225	49,1
07507155/225-220	8,9/8,7	106,7	225/220	48,5
07507155/220-215	8,7/8,5	105,4	220/215	47,9
07507155/215-210	8,5/8,3	104,1	215/210	47,3

1. Dimensions for reference, inch [mm]
2. Delivery and packaging are carried out in accordance with the terms of the contract
3. The manufacturer reserves the right, without notice to the consumer, to make changes to the design of the products for improvement of their technological and operational parameters, which will not affect the quality and properties of the product
4. Deviation of the actual weight of the nominal can be up to 10%.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS SURFACE FINISH: TOLERANCES: ISO 2768 - C LINEAR: ANGULAR:		FINISH:	DEBURR AND BREAK SHARP EDGES	DO NOT SCALE DRAWING	REVISION
DRAWN Kyselytsia		SIGNATURE	DATE 07.07.22	 TITLE: 8" [DN200] Polymer Concrete Channel Pro H8.3"-H12.2" with Cast Iron Grate E600	
CHK'D	MFG				
APPV'D Malynovskiy	MATERIAL: Polymer Concrete, Cast Iron				
Q.A.	WEIGHT: lb / kg				
				ARTICLE:	A3
				SCALE: 1:6	SHEET 1 OF 1