


FLOOR DRAIN FD 150SS - LOAD CLASS A15
EXPOSED CONCRETE PAVEMENT INSTALLATION

6" X 6" (150 X 150 mm) STAINLESS FLOOR DRAIN



NOTES:

1. SPECIFIER IS RESPONSIBLE FOR CONCRETE ENCASEMENT AND REINFORCING BASED UPON APPLICATION AND LOCAL CODES.
2. EXPANSION AND CONTRACTION CONTROL JOINTS AND REINFORCEMENT ARE RECOMMENDED TO PROTECT DRAIN AND CONCRETE SURROUND. ENGINEERING ADVICE MAY BE REQUIRED.
3. THIS INSTALLATION SCHEME IS A RECOMMENDATION. CONSULT WITH THE MANUFACTURER FOR INSTALLATION INSTRUCTIONS.
4. THE FINISH LEVEL OF CONCRETE CLAMP (OR ADJACENT COATING) SHOULD BE 5/64" (2MM) ABOVE THE TOP OF THE DRAIN EDGE.
5. TECHNOLOGICAL SEAM CAN BE MADE WITH A SPECIAL POLYURETHANE SEALANT AS SHOWN ABOVE.

GENERAL: FLOOR DRAIN SHALL BE VODALAND CANADA FD 150SS FLOOR DRAIN AS MANUFACTURED BY VODALAND OR APPROVED EQUAL.

SPECIFICATION: VODALAND FD 150SS FLOOR DRAIN WITH REMOVABLE DEBRIS BASKET AND HYDRO LOCK SYSTEM (TO PREVENT BACK-FLOW OF SEWAGE GASSES) SHALL BE MADE FROM HIGH GRADE 304 STAINLESS STEEL WITH PERFORATED GRATE DESIGN. FLOOR DRAIN SHALL BE A 6" (151 MM) SQUARE, 5.1" (129MM) OVERALL WIDTH AND A 4.00" (102 MM) OUTER DIAMETER OUTLET. FLOOR DRAIN ASSEMBLY SHALL WITHSTAND A REQUIRED EN1433 LOAD CLASS.

MATERIALS: FD 150SS FLOOR DRAIN SHALL BE MANUFACTURED FROM HIGH GRADE 304 STAINLESS STEEL

WATER ABSORPTION	N/A
FROST PROOF	YES
CHEMICAL, ACID & CORROSION RESISTANT	YES
SALT PROOF	YES
ADA COMPLIANT	YES
HIGH TEMPERATURE RESISTANT	YES

THE COMPLETE DRAINAGE SYSTEM SHALL BE BY VODALAND CANADA INC. ANY DEVIATION OR PARTIAL SYSTEM DESIGN AND/OR IMPROPER INSTALLATION WILL VOID ANY AND ALL WARRANTIES PROVIDED BY VODALAND CANADA INC.