

BISHOCKED

Features:

- 200W LED(22 000lm p/Watt)
- 50Ah 12V Battery
- Solar Panel 65W/5V(580 x 350mm)
- 6-8 Hours Charge Time
- 12-16 Hours Discharge Time
- Intelligent Optical Control + Remote Control
- Waterproof Cable
- **U** Frame
- Aluminium + PC Lens
- IP65 Protection Rating
- 10-12 Meters Mounting Height
- Cool White (6500K)
- Can be installed in gardens, residential areas, countryards, roads & parking lots.
- Pole Excluded



Specifications:

Solar Light	200W Solar LED Flood light High Lumen
Solar components	Seperate solar panel, and combined LED light and battery components
Battery	3.2V/50Ah LiFePO4 battery minimum
Lamp Dimensions	254 x 219 x 94mm
Lamp Life	50 000 hours
Luminous Flux	3600lm
Daylight Switch	Yes, incorporated
Cloud conditions	Rainy days and full cloud cover support 3-5 days with full charging
Charging Time	Max. 8 hours with strong sunlight and able to charge on cloudy days
Working/Lighting time	At least 12Hrs
Colour Temperature	6000K
Solar Panel	5V/65W minimum
Water proof Level	IP65 Waterproof Aluminium body, Outdoor use
Mounting Height	10-12 Meters
Installation Distance/spacing	40-50m
Certification	CE, ISO9001 & ROHS
Warranty	5 Years minimum
Lamp body material	Aluminium Alloy





