



A.B.N. 91972197145

FURNITURE WAX SAFETY DATA SHEET

POISONS INFORMATION: 13 11 26

IDENTIFICATION PRODUCT NAME: Finishing Wax

OTHER NAMES: Furniture Wax

PRODUCT CODE: None

UN NUMBER: Not required

DANGEROUS GOODS CLASS: Not required

HAZCHEM CODE: Not required

POISONS SCHEDULE: Not required

PACKAGING GROUP: Not required

EMERGENCY PROCEDURE GUIDE: Not required

USE: Manually applied to timber furniture as a polish and sealant

PHYSICAL DESCRIPTION / PROPERTIES:

APPEARANCE: Pale yellow or white with a slight hydrocarbon odour

BOILING POINT: Approx. 210°C

VAPOUR PRESSURE: 0.5 kPa mm Hg at 38°C

SPECIFIC GRAVITY: 0.73

FLASHPOINT (°C): 65°C

FLAMMABILITY LIMITS (%): LeI 0.6 UeI 7.0

OTHER PROPERTIES: SOLUBILITY: Not soluble in water

MELTING POINT: Approx. 65°C

VAPOUR DENSITY: 5.9 (Air = 1.0)

INGREDIENTS:

Beeswax N/A 10 to 30%

Paraffin Wax 8002-74-2 10 to 30%

Petroleum Hydrocarbons 64771-72-8 40 to 70%

Refined Mineral Oils 68649-95-6 3 to 15%



Eucalyptus Oil 8000-48-4 1 to 2%

Carnauba Wax 2 - 9%

Oil Dyes – White 2653-64-7 0%

Oil Dyes – Black 4197-25-5 0%

HEALTH HAZARD INFORMATION

ACUTE:

Swallowed: May cause irritation to the mouth, throat and stomach

Eye: Harmful to the eyes. Eye irritant

Skin: Contact with the skin may result in irritation. Prolonged or repeated contact with skin may lead to dermatitis effects

Inhaled: Low toxicity and not a normal feature of this product

CHRONIC: None Known

FIRST AID:

Swallowed: Remove material from mouth. Rinse mouth thoroughly with water. Drink 1 or 2 glasses of water (or milk). Do not induce vomiting. Obtain medical attention

Eye: Hold eyelids open and flush with water for at least 15 minutes, then obtain medical attention

Skin: Wash skin thoroughly with water. Remove contaminated clothing. Obtain medical attention if irritations occur

Inhaled: Remove to fresh air. Keep warm and seek medical advice

FIRST AID FACILITIES: Emergency eyewash station and shower

ADVISE TO DOCTOR: Treat symptomatically

PRECAUTIONS FOR USE

EXPOSURE STANDARDS: TLV, No exposure limits set by National health and Medical Research. Up to 300ppm recommended per 8hr/day/5days

ENGINEERING CONTROLS: Use in ventilated areas

PERSONAL PROTECTION: Avoid contact with skin and eyes. Wash hands after use

CLOTHING: Overalls recommended

GOGGLES: Eye protection recommended

GLOVES: Solvent resistant gloves recommended All safety equipment should comply with Australian Standards or an equivalent approved by a State or Territory Authority



FLAMMABILITY: Combustible, vapours may create flammable / explosive atmosphere on heating above flash point

SAFE HANDLING INFORMATION

STORAGE TRANSPORT: Keep containers securely sealed and protected against damage. Non regulated goods. Store in a cool place and away from naked flames and heat

SPILL AND DISPOSAL: Eliminate sources of ignition, shovel up and place in an approved container for disposal. Use absorbent material if required. Consult local authorities for disposal

Note: Precautions to be observed by clean up crew – protective clothing **MUST** be worn. Care should be taken not to slip on contaminated area

FIRE / EXPLOSION HAZARD: Use foam, dry chemical, Carbon Dioxide or water fog. Keep product out of sewer and water courses

OTHER INFORMATION: Do not store near oxidising agents

OTHER INFORMATION Before being marketed, products are carefully screened for potential hazard to the user, and where necessary, a warning or advice for use is on the label. However, as with all chemicals, if improperly used the products can be harmful, hence guidelines and recommendations for first aid treatment are provided.