

# TERAFLEX

## INSTALLATION GUIDE

### Installation Guide for the TeraFlex JK Wrangler RockGuard Rock Sliders



**Note** The rock sliders were designed specifically for the JK Wrangler 2 door or 4 door models.

p/n 004637300

fits 2 door

p/n 004637310

fits 4 door

#### INSTALLATION:

1. Remove the factory steps from each side of the vehicle.



4. Drill a 25/64 hole at each mark to prepare for installation of the nut inserts. Install the nut inserts along the body using an appropriate insert tool.

**Note:** avoid drilling into the wiring harness along the bottom of the door when drilling all the holes.

2. Put tape along the body under the door to protect the paint.



3. Hold the new rock slider up in place and mark all the holes on the tape using a black marker.



**Tera Manufacturing, Inc.**  
5251 South Commerce Dr.  
Murray, Utah 84107  
Phone/801.288.2585  
Fax/801.713.2313  
www.teraflex.biz



- Put the rubber seal along the top edge of the rock slider and cut to length. Install the slider along the body with the stainless button head bolts.



- With the body side bolts installed, mark and drill up through the bottom of the rock slider and install the long through bolts.  
**Note:** Pull back the carpet to prevent damage to the carpet.



- Install the plastic end caps included with the kit

**Note:** Some of our kits include a tool for the nut insert. Read and follow the instructions for each individual nut insert tool for proper installation

#### MAINTENANCE INFORMATION:

It is the buyer's responsibility to have all suspension, drivetrain, steering, and other components checked for proper tightness and torque after the first 100 miles and every 3000 miles after that.

#### NOTICE TO INSTALLER:

The enclosed "Warning to Driver" sticker must be installed in the vehicle in driver's view. This sticker is to act as a constant safety reminder when operating the vehicle. It is your responsibility as the equipment installer to install the provided sticker and to forward these instructions to the vehicle's owner for review, and product information. If a "Warning to Driver" sticker was not included in this kit, FREE replacement stickers are available by request. It is the installer's duty to ensure a safe and controllable vehicle after the modifications have been performed.

#### WARNING:

Neither the seller nor the manufacturer will be liable for any loss, damage, or injury directly or indirectly arising from the use of or inability to determine the use of these products. Before using, the user shall determine the suitability of the products for its intended use, and the user shall assume all responsibility and risk in connection therewith.

#### TERAFLEX WARRANTY:

Tera Manufacturing warrants TeraFlex products to the original retail purchaser to be free of defects in material and workmanship for as long as the original purchaser owns the vehicle on which products were originally installed.

Failure to complete regular maintenance (grease every 3,000 miles) on TeraFlex FlexArms will void this warranty. All other conditions of the standard Tera Mfg. product warranty apply.

All TeraLow products are covered by Tera's two-year warranty to be free of defects in material and workmanship for two years from date purchased.

Tera axles are covered by a 12-month warranty to be free of defects in materials and workmanship.

This warranty does not cover or include product finish, improperly installed or applied products, improperly maintained products, used for racing or competition or damage due to abuse or neglect.

All returns must be accompanied by an original invoice. It is the customer's responsibility to remove the product from the vehicle. Shipping charges are the responsibility of the customer. Tera Manufacturing will pay the return freight.