## Alcor LED MR16 - 3W

## High-Power LED Spot Lamp

Project Name: \_\_\_\_\_\_

Catalog No.: \_\_\_\_\_\_

Date: \_\_\_\_\_



### Dimensions





#### **Features**

- ENERGY SAVING
- Retrofits 25 Watt halogen MR16s
- 35K hours of continuous light output
- Consumes a fraction of energy than halogen MR16s
- Low voltage power requirements
- Finely tuned optic lens provides solid elliptical beams
- Built-in LED Driver
- Mercury free, lead free, and RoHS compliant
- UL Listed for U.S. and Canada

#### **Product Specifications**

LED Type High-Power 1W LEDs
LED Brand Philips or Samsung

SocketType GU5.3

Power Requirement 12V AC/DC

Power Consumption 3 Watts

Compatibility Magnetic & Most Electronic Transformers

Beam Angles 25°, 40°, 60° Number of LEDs 1 LEDs

Hours 35K Hrs Maintenance-Free

Rating Indoor Applications

Housing Optimized Heat Dissipating Aluminum,

Machine-Cut & Silver Satin-Anodized


Lumen Maintenance 70% of Original Light Ouput @ 30K Hrs


Operating Temp  $-40^{\circ}$  F  $(-40^{\circ}$  C) to  $104^{\circ}$  F  $(40^{\circ}$  C)

Warranty 3Years

Certification UL Listed (U.S. & Canada)

RoHS Compliant





#### Output

	Warm White	Cool White	
Color Temperatures	3000K	4300K	6000K
Lumens	120	150	158
CRI	80	75	70

#### **Applications**

- Halogen MR16 Retrofits
- Track Lighting Systems
- Trade Show Exhibits
- Residential Interiors
- Commercial Interiors
- Cabinet Lighting
- Merchandising Displays
- Kitchen & Bath
- Shelves

# Alcor LED MR16 - 3W

High-Power LED Spot Lamp









## **Ordering Information**

Alcor MR16 LED Spotlamps - 3 Watts - Non Dimmable									
Cat. No.	Watts	# of LEDs	Beam Angle	Lumens	Voltage	Socket Type	Color Temperature		
ALM16003012W	3	1	25°	120	12V AC/DC	GU5.3	3000K Warm White		
ALM16003014W	3	1	40°	120	12V AC/DC	GU5.3	3000K Warm White		
ALM16003016W	3	1	60°	120	12V AC/DC	GU5.3	3000K Warm White		
ALM16003012N	3	1	25°	150	12V AC/DC	GU5.3	4300K Neutral White		
ALM16003014N	3	1	40°	150	12V AC/DC	GU5.3	4300K Neutral White		
ALM16003016N	3	1	60°	150	12V AC/DC	GU5.3	4300K Neutral White		
ALM16003012C	3	1	25°	158	12V AC/DC	GU5.3	6000K Cool White		
ALM16003014C	3	1	40°	158	12V AC/DC	GU5.3	6000K Cool White		
ALM16003016C	3	1	60°	158	12V AC/DC	GU5.3	6000K Cool White		

#### NOTE

All specifications are subject to change without notice. We reserve the right to alter or change our products without notice. Lumens are calculated based on  $40^{\circ}$  beam pattern.