

SIMPLY CONSERVE

LED UFO HIGH BAY

L130HBU50D, L175HBU50D



The UFO High Bay is the ideal solution for commercial spaces with high ceilings. Its damp-rated durability is appropriate for illuminating a wide range of spaces, including warehouses, gymnasiums, manufacturing facilities and more. With minimal glare and optimal performance, the UFO High Bay is the energy-efficient solution to replace outdated commercial lighting.



PRODUCT FEATURES OVERVIEW



DAMP-RATED



MERCURY-FREE



INSTANT-ON/OFF



0-10V DIMMABLE



5-YEAR LIMITED WARRANTY*

*AM Conservation Group, Inc. guarantees to the original purchaser or recipient of this lamp that it is free from defects in material and workmanship for five years from the date of purchase. Warranty is limited to repair or replacement of the lamp. Lamps being returned must include proof of purchase.

Input Power (W):	130W (L130HBU50D) 175W (L175HBU50D)
Color Temp (CCT):	5000K
Typical Lumens (lm):	17,000 lm (L130HBU50D) 27,000 lm (L175HBU50D)
Efficacy (lm/w):	131 lm/w
Beam Angle:	120°
Operation Temperature:	-31°F - 104°F
Storage Temperature:	-31°F - 104°F
Input Voltage (V):	120-277V
Power Factor:	> 0.9
THD:	20%
Ignition Time:	Instant-On
Line Frequency:	60 Hz
Dimmable:	0-10V
Safety Certification:	ETL

DLC-Listed:	Yes
Product Life:	50,000 Hrs
Base / Cap:	N/A
Target Replacement:	400W Metal Halide (L130HBU50D) 600W Metal Halide (L175HBU50D)
• Wet Location	
• Aluminum Construction	

LED UFO HIGH BAY | L130HBU50D, L175HBU50D

SPECIFICATIONS BY MODEL

ITEM #	WATTS	CCT	LUMENS	PF	CRI	LIFETIME	BEAM ANGLE	VOLTAGE	SHAPE	CERTIFICATIONS
L130HBU50D	130W	5000K	17,000 lm	≥0.9	80	50,000 Hrs	120°	120-277V	Round	DLC Standard
L175HBU50D	175W	5000K	23,000 lm	≥0.9	80	50,000 Hrs	120°	120-277V	Round	DLC Standard

MODEL SELECTION

FAMILY	WATTAGE	LAMP TYPE	SHAPE	CCT.
L = LED Linear	130 = 130W 175 = 175W	HB = High Bay	U = UFO (Round)	50 = 5000K

DIMENSIONS

PRODUCT (L130HBU50D)

8 5/16"

8 1/2" MAX

PACKAGING

Case

9 7/8"

9 7/8"

8"

1/Master Case Gross WT: 9 1/2 LBS

PRODUCT (L175HBU50D)

9 7/8"

8 11/16"

PACKAGING

Case

11 7/8"

11 7/8"

8 1/2"

1/Master Case Gross WT: 12 1/4 LBS