

# ProTex™

Protection Tissue

## THERMAL TRANSFER TISSUE

### FEATURES:

- Longer roll lengths
- Lower basis weight
- Natural color
- Formaldehyde-free
- High gas barrier sheet with heat resistance
- Neutral ph
- Wrinkle-free wind
- High tensile strength
- Recyclable

*ProTex™ tissue's high density, neutral ph and formaldehyde-free composition provides the highest yield and the strongest barrier protection possible. With more widths and diameters in stock, we have you covered!*

### CUSTOMER BENEFITS:

- Fewer roll changes, less downtime.
- Reduces purchase transport, storage, and disposal costs.
- No bleaching agents, less harmful to the environment.
- Eliminates a major cause of heat induced textile yellowing.
- Extends the life of the calender belt by blocking excess dye-gas.
- Retains most tensile strength after prolonged exposure to heat.
- Prevents transferred crease marks.
- Reduces web tear-outs.
- 100% recyclable ingredients.

### Properties

Grade	GSM	Thickness	Applications
ProTex 19	19 gsm	36μ / .0014"	All heat press calender transfers.
ProTex 25	25 gsm	43μ / .0017"	All heat press calender transfers.

<b>Thermal Transfer Tissue Approx. Weight Per Roll</b>				
<b>11.5 POUND (19 GRAM)</b>				
<b>Roll Widths</b>	<b>16" Diameter</b>	<b>12" Diameter</b>	<b>10" Diameter</b>	<b>8" Diameter</b>
36" (.914 m)	186 lbs.	97 lbs.	69 lbs.	38 lbs.
40" (1.01 m)	207 lbs.	107 lbs.	77 lbs.	42 lbs.
48" (1.21 m)	248 lbs.	129 lbs.	92 lbs.	51 lbs.
54" (1.37 m)	279 lbs.	145 lbs.	104 lbs.	57 lbs.
60" (1.55 m)	311 lbs.	161 lbs.	115 lbs.	63 lbs.
64" (1.63 m)	331 lbs.	172 lbs.	123 lbs.	68 lbs.
66" (1.67 m)	342 lbs.	177 lbs.	127 lbs.	70 lbs.
68" (1.72 m)	351 lbs.	182 lbs.	130 lbs.	72 lbs.
72" (1.83 m)	373 lbs.	193 lbs.	138 lbs.	76 lbs.
80" (2.03 m)	414 lbs.	214 lbs.	153 lbs.	84 lbs.
96" (2.43 m)	497 lbs.	258 lbs.	184 lbs.	101 lbs.
104" (2.64 m)	538 lbs.	278 lbs.	199 lbs.	110 lbs.
Yards per roll	5400 yds.	2800 yds.	2000 yds.	1100 yds.
Feet per roll	16,200 ft.	8400 ft.	6000 ft.	3300 ft.
<b>15 POUND (25 GRAM)</b>				
<b>Roll Widths</b>	<b>16" Diameter</b>	<b>12" Diameter</b>	<b>10" Diameter</b>	<b>8" Diameter</b>
126" (3.2 m)	661 lbs.	347 lbs.	244 lbs.	126 lbs.
130" (3.3 m)	680 lbs.	356 lbs.	251 lbs.	129 lbs.
Yards per roll	4200 yds.	2200 yds.	1550 yds.	800 yds.
Feet per roll	12,600 ft.	6600 ft.	4650 ft.	2400 ft.

\* Additional widths and diameters available upon request, ask your sales representative.

**Contact us about our sublimation media products**

- TexPrint® Sublimation Print Paper
- ProTex™ Protection Tissue
- TexStyles® Graphic Fabrics
- TexSewn™ Cut & Sew Paper

**Contact Customer Service & Sales**

770-935-5080 x1  
 1-800-768-2700  
 orders@beaverpaper.com  
 info@beaverpaper.com

**Beaver Paper & Graphic Media, Inc., HQ**

2420 Tech Center Parkway, Bldg. 140  
 Lawrenceville, GA 30043 USA

**Beaver Paper & Graphic Media, Inc., West Coast**

3170 Slauson Ave.  
 Vernon, CA 90058 USA

**Beaver Paper GmbH**

Im Lossenfeld 19  
 77731 Willstätt, Germany