



Chemical Consultants INCORPORATED

IW-108

Multi-Purpose Screen Wash

GENERAL DESCRIPTION

IW-108 is a water soluble ink degradant. It is highly effective on plastisol, multi-purpose (solvent based), poster, UV, and vinyl inks. IW-108 will protect the fabric from deep stains or ghosting from the image print. This makes it much easier when complete reclamation of the screen is necessary.

IW-108 can be used in a wide variety of innovative cleaning processes ranging from re-circulation machines, dip tanks, immersion cleaning processes, and automatic reclaiming machines. It can also be applied manually with a scrub pad, spray bottle, or pneumatic pump systems.

IW-108 is also an excellent plastisol ink haze (ghost) remover. It is non-hazardous (non-corrosive) and aggressively removes image stains from the mesh.

ADVANTAGES

- Low Odor
- High Solvency
- High load capacity to reduce usage
- High flash point / Non-flammable
- Non-Hazardous
- Mesh safe
- Multiple applications


APPLICATIONS

Always card excessive ink from screen. Use one of the following applications.

Quick Tip:

Always pressure wash screen from the bottom and work upwards.

This will prevent ink from locking back onto the mesh when coming in contact with the rinse water.



INK WASH-OUT AT THE SINK:

Card excessive ink from the screen. Apply IW-108 to ink side of screen. Use a non-abrasive scrub brush or pad to agitate ink on both sides of screen. Finally, rinse away all residue away using high pressure water.

Packaging

1 gallon 5 gallon pail 55 gallon drum

Haze Remover:

After ink and emulsion has been removed, spray IW-108 on both sides of the screen. Scrub screen both sides with a non-abrasive brush or pad. Allow product to dwell a few minutes (depending on severity of stain). High pressure rinse screen working from bottom and moving upwards.

4 x 4 Stainless Steel Recirculating Booth

[Click here for more details.](#)

RECIRCULATING WASH:

Card excessive ink from the screen. This product can be continuously recirculated until product becomes too heavily soiled with solids. Used product may be filtered and reused.

