



# DIGITAL MEDIA APPLICATION INSTRUCTIONS

## **ColorPrint PU** (Matte/Gloss) For Use On: 100% cotton | Poly/cotton blends | 100% polyester | Leather | Lycra®/Spandex



### **Print and Cut Instructions:**

- Set heater/dryer to 113°F/45°C
- If heavy saturation ink, dry 1 hour before cutting
- Print, cut, and weed material
- Mask with TTD Easy mask or TTD High Tack Mask

### **Application Instructions:**

- Preheat garment for 2-3 seconds
- Apply design at 295°F / 146°C
- Use medium pressure for 15-20 seconds
- Peel carrier hot

### **Laundering:**

- Wait 24 hours before first wash
- Machine wash warm or cold with mild detergent
- Do not bleach or dry clean
- Dry on normal dryer setting

**Compatible with Eco-Solvent, Solvent, and Latex Inks - Not compatible with Inkjet or Laser printers**

## **ColorPrint Easy** For Use On: 100% cotton | Poly/cotton blends | 100% polyester | Leather



### **Print and Cut Instructions:**

- Print, cut, and weed material
- No dry time required!
- Mask with TTD Easy mask or TTD High Tack Mask

### **Application Instructions:**

- Preheat garment for 2-3 seconds
- Apply design at 300°F / 149°C
- Use medium pressure for 15 seconds
- Peel carrier warm

### **Laundering:**

- Wait 24 hours before first wash
- Machine wash warm or cold with mild detergent
- Do not bleach or dry clean
- Dry on normal dryer setting

**Compatible with Eco-Solvent and Solvent Inks - Not for use with Inkjet or Laser printers**

## **ColorPrint Extra PU** For Use On: 100% Nylon | 100% cotton | Poly/cotton blends | 100% polyester | Leather

### **Print and Cut Instructions:**

- Print, cut, and weed material
- No dry time required!
- Mask with TTD Easy mask or TTD High Tack Mask

### **Application Instructions:**

- Preheat garment for 2-3 seconds
- Apply design at 305°F / 150°C
- Use medium pressure for 15 seconds
- Peel carrier hot or warm

### **Laundering:**

- Wait 24 hours before first wash
- Machine wash cold with mild detergent
- Do not bleach or dry clean
- Wash inside-out for best results

**Compatible with Eco-Solvent, Solvent, and Latex Inks - Not compatible with Inkjet or Laser printers**

## **ColorPrint Extra** For Use On: 100% Nylon | 100% cotton | Poly/cotton blends | 100% polyester | Leather

### **Print and Cut Instructions:**

- Print, cut, and weed material
- No dry time required!
- Mask with TTD Easy mask or TTD High Tack Mask

### **Application Instructions:**

- Preheat garment for 2-3 seconds
- Apply design at 320°F / 160°C
- Use medium pressure for 10-15 seconds
- Peel carrier hot

### **Laundering:**

- Wait 24 hours before first wash
- Machine wash cold with mild detergent
- Do not bleach or dry clean
- Dry on normal dryer setting

**Compatible with Eco-Solvent, Solvent, and Latex Inks - Not compatible with Inkjet or Laser printers**

## **ColorPrint Soft Opaque** For Use On: 100% cotton | Poly/cotton blends | 100% polyester | Leather



### **Print and Cut Instructions:**

- Set cutter force to 30-50 grams to ensure the design
- will remove from mask  
Allow 30 minutes to 1 hour dry time for detailed designs
- Print, cut, and weed material
- Mask with TTD High Tack Mask

### **Application Instructions:**

- Preheat garment for 2-3 seconds
- Apply design at 311°F / 155°C
- Use medium/firm pressure for 15 seconds
- Peel carrier Hot.

### **Laundering:**

- Wait 24 hours before first wash
- Machine wash cold with mild detergent
- Do not bleach or dry clean
- Dry on normal dryer setting

**Compatible with Eco-Solvent and Solvent Inks - Not compatible with Inkjet or Laser printers**

## **Sublithin® Soft** For Use On: Sublimated | polyester 100% cotton | Poly/cotton blends | 100% polyester



### **Print and Cut Instructions:**

- Print, cut, and weed material
- Mask with TTD Easy Mask

### **Application Instructions:**

- Preheat garment for 2-3 seconds
- Apply design at 265°F / 130°C
- Use medium pressure for 15 seconds
- Peel carrier warm

### **Laundering:**

- Wait 24 hours before first wash
- Machine wash cold with mild detergent
- Do not bleach or dry clean
- Hang item to dry

**Compatible with Eco-Solvent, Solvent and Latex Inks - Not compatible with Inkjet or Laser printers**

## **Hi-5 Print Matte** For Use On: 100% cotton | Poly/cotton blends | 100% polyester



### **Print and Cut Instructions:**

- Print, cut, and weed material
- Mask with TTD Easy Mask or TTD High Tack Mask

### **Application Instructions:**

- Preheat garment for 2-3 seconds
- Apply design at 250°F / 120°C
- Use medium pressure for 5 seconds
- Peel carrier hot

### **Laundering:**

- Wait 24 hours before first wash
- Machine wash cold with mild detergent
- Do not bleach or dry clean
- Dry on normal dryer setting

**Compatible with Eco-Solvent, Solvent, and Latex Inks - Not compatible with Inkjet or Laser printers**



SiserNA.com