

Grabcon® Frame

GRABCON®
CONCRETE FRAMING SCREW

FREE!
TX40
Driver bit
Included

**Fast, Efficient
Bottom Plate Fixing!**

- For fixing timber to concrete or brick/ blockwork
- Domed washered head for high clamping force
- Non-expansion for close to concrete edge
- Can also be used for timber to timber applications
- Fully removable design (nothing left in the concrete)

Performance derived in accordance with
AS 1720.1 - 2010 (timber Structures)

ZINC

GAL

Grabcon® Frame

Grabcon® Concrete Framing Screw - Zinc Clear

Grabcon® Concrete Framing Screw - Galvanised **NEW**

Part No.	Part No.	Description	mm	drive	mm	qty	qty
GCF0610Z	GCF0610ZG	6 x 102mm Concrete frame screw	6	T40	up to 45	100	1000

Grabcon Frame Specification details					Recommended Load 20 MPa Concrete (min.)		
Product	Description	Drill dia. (mm)	Head Dia. (mm)	Embedment Depth (mm)	Tension (kN)	Spacing Min. (mm)	Edge Distance Min. (mm)
Frame Screw	6 x 102	6	21	57	1.45	200	45
					2.00	200	200

Note: The Grabcon Frame screw anchor has been tested for pull-through capacity as referenced in AS 1720.1-2010.
 Maximum Recommend Load (pull-through / 35mm MGP10) = 3.4kN
Zinc Coating: 5 µm minimum. **Galvanised Coating:** 42 µm minimum.

ICCONS Pty Ltd.
 Head Office, 12-18 Produce Drive,
 Dandenong South, Victoria, 3175

P: 03 9706 4344
 F: 03 9768 3329
 E: info@iccons.com.au

