



COMPLIANT ANCHORING SOLUTIONS

Mechanical Anchors	National Code Compliant	European Technical Assessment	Cracked Concrete Approval	C1 Earthquake Seismic Approval	C2 Earthquake Seismic Approval	Fire Rated	CE Certification	Load Performance	Overhead Applications	Size range approved	Coating / Material	Product Guide Page No.
	ATS-EVO S Hex Head ¹										M6 - M24	CLEAR ZINC
ATS-EVO SK Countersunk Head ¹										M6 - M12	CLEAR ZINC	20
FM-753® Crack Nautilus ¹										M8 - M16	NAUTILUS® +1000h	23
FM-753® Crack (A4 316 SS) ¹										M8 - M16	316 SS	23
TSM High Performance ¹										6mm - 14mm	CLEAR ZINC 316 SS	27
TB1-Plus Thru Bolt ¹										M8 - M16	CLEAR ZINC	24
TB1-A4-Plus Thru Bolt (A4 316 SS) ¹										M8 - M12	316 SS	24
SB2-Plus Screwbolt ¹										8mm - 14mm	GALVANISED	26
Di-Lip-Plus & Di-Plus Drop-in Anchor ²										M8 - M12	CLEAR ZINC	39
FM-X5 Nylon Frame Fixing ³										Ø10mm (85mm - 160mm)	NAUTILUS® +1000h 316 SS	51
TPP Hammer Screw ³										Ø5.6, 8mm	CLEAR ZINC 304 SS	46

Mechanical Anchors	National Code Compliant	European Technical Assessment	Cracked Concrete Approval	C1 Earthquake Seismic Approval	C2 Earthquake Seismic Approval	Fire Rated	CE Certification	Load Performance	Overhead Applications	Size range approved	Coating / Material	Product Guide Page No.
	CA-Plus Ceiling Anchor ²										Ø6 x 35mm	CLEAR ZINC
TSM IM Internal Thread Anchor ¹										M10 Internal Thread (Ø6mm)	CLEAR ZINC	41
TSMB External Thread Anchor ¹ - available with M12 coupler - sold separately										M8 External Thread (Ø6mm)	CLEAR ZINC	41
TSO Spring Anchor ²										TSO (Ø6 x 40mm)	CLEAR ZINC	35

NCC MECHANICAL RANGE

NCC MECHANICAL RANGE

Chemical Anchors	National Code Compliant	European Technical Assessment	Cracked Concrete Approval	C1 Earthquake Seismic Approval	C2 Earthquake Seismic Approval	Fire Rated	CE Certification	Load Performance	Overhead Applications	Water Filled Holes	Core Drilled Holes	Masonry/Brickwork	Rebar	Threaded Stud / Insert	Working Time MINS @ 20°C (Dry Holes)	Curing Time MINS @ 20°C (Dry Holes)	VOC (Green Building)	Product Guide Page No.
	BIS-P POLYESTER 300mL / 420mL ¹ CODE BLUE															6	45	
BIS-V VINYLESTER 300mL / 420mL ¹ CODE GREEN															6	45		71
BIS-HY HYBRID 280mL / 420mL ¹ CODE PLATINUM															3	30		69
BIS-PE PURE EPOXY 385mL / 585mL ¹ CODE RED															30	10 hrs		67
VDP-Q CAPSULE VINYLESTER M8 - M24 ¹ CODE GOLD															unlimited	20		75

NCC CHEMSELECT RANGE

¹ Product complies with SA TS 101:2015 (Design of post-installed and cast-in fastenings for use in concrete) and ETAG 001 Part 1 - 5 as relevant. ² Product complies with with ETAG 001 Part 6 (Anchors for multiple use for non-structural applications). ³ Product complies with ETAG 020 Annex C (Plastic anchors for use in concrete and masonry for non-structural applications).