

Grabcon[®] Door & Window Screws

NEW!



Grabcon[®] FLAT COUNTERSUNK Concrete & Masonry Screws

Ideal for metal door & window installation



■ Carbon Steel Galvanised



GALVANISED Part No.	Description	Drill Diameter (mm)	Min. Anchor Embedment (mm)	Drill Depth (mm)	Max. Fixture Thickness (mm)	Drive Type (Torx)	 qty	 qty
SKSZ06042G	6 x 42mm	6	30	40	12	T30	100	400
SKSZ06062G	6 x 62mm				32		100	400
SKSZ06072G	6 x 72mm				42		100	400
SKSZ06092G	6 x 92mm				62		100	400
SKSZ06112G	6 x 112mm				82		50	200

Grabcon Specification details									Recommended Loads 25 MPa Concrete (min.)			
Product	Description	CSK Head dia. (mm)	CSK Head Height (mm)	CSK Head angle	Clearance hole in Fixture (mm)	Drill dia. (mm)	Embedment Depth (mm)	Drill depth (mm)	Tension (kN)	Shear (kN)	Spacing (min.)	Edge Distance (min)
Door and Window Screw	6 x 42	11.5	3.7	45°	8	6	30	40	0.9	0.5	60	45
	6 x 62	11.5	3.7	45°	8	6	30	40	0.9	0.5	60	45
	6 x 72	11.5	3.7	45°	8	6	30	40	0.9	0.5	60	45
	6 x 92	11.5	3.7	45°	8	6	30	40	0.9	0.5	60	45
	6 x 112	11.5	3.7	45°	8	6	30	40	0.9	0.5	60	45

ICCONS Pty Ltd.

Head Office, 383, Frankston Dandenong Road,
Dandenong South, Victoria, 3175

P: 03 9706 4344

E: info@iccons.com.au

