## **Product Description**

The 12500 Watt generator is ideal for home backup and jobsite power. The unit features a 22 HP Subaru Electric Start V-Twin OHV gas engine with low-oil shutdown. The 8 gallon gas tank with fuel gauge runs up to 6 hours at 50% load. The control panel contains (4) 120V 20A GFCI protected outlets, (1) 120/240V 50A outlet, (1) 120V 30A twistlock outlet, and circuit breaker protection. The idle control feature reduces fuel consumption when power is not being pulled from the generator. The unit is equipped with 13 inches pneumatic wheels and dual folding handles for easy portability. It includes (2) 1 quart bottles of oil and 12V 34AH battery.

- 12500 Running watts, 15625 maximum watts
- Electric start 22 HP Subaru V-Twin OHV gas engine with low-oil shutdown
- 8 gal. Gas tank with fuel gauge
- Control panel includes (4) 120V 20A GFCI protected outlets, (1) 120/240V 50A outlet and (1) 120V 30A twist lock outlet and circuit breaker protection
- Click on the "More Info" tab to download the specifications pdf to view the wattage requirement guide

## **SPECIFICATIONS**

Amperage (amps)	104.2 A	Assembled Depth (in.)	39 in
Assembled Height (in.)	30 in	Assembled Width (in.)	22 in
Auto idle control	Yes	Automatic Voltage Regulation	No
Built-in inverter	No	CSA Listed	No
Continuous Wattage	12500	ETL Listed	No
Engine Displacement (cc)	653	Engine manufacturer	Subaru
Fuel Gauge	Yes	Fuel tank capacity (gallons)	8.0
Fuel type	Gasoline	Full load fuel consumption (gallons/hour)	0.0

Horsepower (hp)	22 hp	Low oil shutdown	Yes
Manufacturer Warranty	2 years	Muffler	Yes
Number of circuits/outlets	4	Operational volume (dB)	82.0
Osha Required GFCI Outlets	Yes	Output Receptacles	120V 5-20R GFCI (2), 120V L5-30R (1), 120-240V 14-50R (1)
Peak Wattage	15625	Product Height (in.)	30.0
Product Length (in.)	39 in	Product Weight (lb.)	360
Product Width (in.)	22 in	Rated Wattage	12500
Returnable	30-Day	Run time at 50% load (hours/tank)	6
Sell Pack (Baby)	8018539055851	UL Listed	N-No UL Code Rating
Voltage Rating	120/240 V.		