PRODUCT:

OPULENT OPTIC PENDANTS

TECH SPEC

Last updated: 19.12.2022 (VR)

PRODUCT

Manufactured to BS EN 60598-1:2015

WEB LINK: → rothschildbickers.com/opulent-optic LAMPHOLDER: Standard: E14 or E12 (USA) / SES bulb Large: E27 or E26 (USA) /ES bulb ELECTRICAL: AC 220-240V Nominal frequency 50Hz AC 110 0 120V Normal frequency 60Hz (USA) MAX WEIGHT INC. 2M FLEX Standard/Large 1.4 - 1.7kg STANDARD CEILING ROSE: Petite, Empire or Classic rose included -→ rothschildbickers.com/ceiling-roses

*For all USA a larger 4.7 inch ceiling canopy is provided to fit over a connector box which is not supplied.



OPTIONS

SHAPE: Standard, Large METAL FINISH: Standard colours + rothschildbickers.com/metal FLEX: Standard colours & styles (3 core) + rothschildbickers.com/flex Supplied standard with 1.5m (can be cut on site) Extra length up to 12m on request GLASS COLOUR: Standard colours -+ rothschildbickers.com/glass-colours GLASS FINISH: Optic only STANDARD TRIMMING COLOURS:

→ rothschildbickers.com/trimmings



