

PRODUCT:

## STANDING PENDANTS

TECH SPEC

Manufactured to BS EN 60598-1:2015

Last updated: 12.12.2022 (VR)

### PRODUCT

WEB LINK:

→ [rothschildbickers.com/standing-pendant](https://rothschildbickers.com/standing-pendant)

LAMPHOLDER:

E14 or E12 (USA) / SES bulb

ELECTRICAL:

AC 220-240V Nominal frequency 50Hz

AC 110 O 120V Normal frequency 60Hz (USA)

MAX WEIGHT INC. 2M FLEX

Standard: 1.4kg

STANDARD CEILING ROSE:

Petite, Empire or Classic rose included -

→ [rothschildbickers.com/ceiling-roses](https://rothschildbickers.com/ceiling-roses)

\*For all USA a larger 4.7 inch ceiling canopy is provided to fit over connector box which is not supplied.



### OPTIONS

SHAPE:

Standard

METAL FINISH:

Polished Copper & Nickel and Antique Brass only

FLEX:

Standard colours & styles (3 core)

→ [rothschildbickers.com/flex](https://rothschildbickers.com/flex)

Supplied standard with 1.5M - can cut to length on site

Extra length up to 12M on request

GLASS COLOUR:

Standard colours -


→ [rothschildbickers.com/glass-colours](https://rothschildbickers.com/glass-colours)

GLASS FINISH:


Plain only

### INCLUDED IN THE BOX

- 1 x Glass shade
- 1 x Electrical loom wired with flex
- 1 x Standard ceiling canopy
- 1 x Ceiling rose bracket, screws and washers
- 3 x Wago Connectors or junction box
- 1 x E14 LED Bulb (UK/EU only)
- \*No bulb supplied for USA (self-ballasted LED lamp)
- 1 x Installation guide



### DIMENSIONS



STANDARD