PRODUCT:

SPINDLE PENDANTS

TECH SPEC

Last updated: 12.12.2022 (VR)

PRODUCT

WEB LINK:

→ rothschildbickers.com/spindle-pendant

LAMPHOLDER:

E14 or E12 (USA) / SES bulb

Manufactured to BS EN 60598-1:2015

ELECTRICAL:

AC 220-240V Nominal frequency 50Hz AC 110 0 120V Normal frequency 60Hz (USA)

MAX WEIGHT INC. 2M FLEX Standard: 1.4kg
STANDARD CEILING ROSE:

Petite, Empire or Classic rose included -

→ rothschildbickers.com/ceiling-roses

*For all USA a larger 4.7 inch ceiling canopy is provided to fit over connector box which is not supplied.

OPTIONS

SHAPE:

3 Bubble, 4 Bubble

METAL FINISH:

Standard colours → rothschildbickers.com/metal

FI FX:

Standard colours & styles (3 core)

→ rothschildbickers.com/flex

Supplied standard with 1.5M - can cut to length on site

Extra length up to 12M on request


GLASS COLOUR: Clear only

GLASS FINISH: Optic only



INCLUDED IN THE BOX

- 1x Glass shade
- 1x Electrical loom wired with flex
- 1x Standard ceiling canopy
- 1x Ceiling rose bracket, screws and washers
- 3 x Wago Connectors or junction box
- 1 x E14 LED Bulb (UK/EU only)
- *No bulb supplied for USA (self-ballasted LED lamp)
- 1x Installation guide



Attaching shade

#