

### PRODUCT INFORMATION

NAME	Concrete+ Typhoon 2.5™
MODEL NUMBER	FZVACE-2.5
MSRP	\$364.49
UPC / BARCODE	850020839339



### PRODUCT IMAGE



### DESCRIPTION

Easily switch from delivering water through tools to spraying chemicals such as curing compounds, form release, cleaning chemicals, pesticides and more. Powered by a 18V lithium-ion battery, this sprayer results in 2-3x more efficiency than a manual sprayer. Plus operate continuously for up to 3 hours and spray more than 76 gallons per battery charge at a distance of 30 feet.

To view the most updated operation guide visit: [www.fzspray.com/operation-guides](http://www.fzspray.com/operation-guides) or scan the QR code



### WHAT'S INCLUDED

	PART NUMBER	PART NUMBER
18/5.2Ah LI-ION BATTERY	FZAAEM	GHT-GHT UV-RESISTANT 5-FT HOSE
21V/2.5A BATTERY CHARGER	FZAAEL	ADJUSTABLE CONE NOZZLE
STAINLESS-STEEL WAND	FZRAAS	0° PIN STREAM NOZZLE
SPRAY GUN	FZRACN	25° FAN NOZZLE
COMFORTSTRAPS™	FZAAGE	

### LOGISTICAL INFORMATION

GROSS / NET WEIGHT	16 / 14 pounds	PALLET QUANTITY	36 units
PACKAGE SIZE	14" x 9.5" x 21.7"	20' GP QUANTITY	420 units
WEIGHT PER UNIT	16 lbs	40' GP QUANTITY	840 units
WEIGHT PER PALLET	627 lbs	40' HQ QUANTITY	1080 units

### PRODUCT SPECIFICATIONS

TANK TYPE	4-Gallon Backpack		GUN / WAND TYPE	GHT Pressure Washer Spray Gun with Viton™ Seal / Quick-Connect Stainless Steel Wand	
PUMP TYPE	Heavy-Duty Diaphragm Pump		BATTERY VOLTAGE/CAPACITY	18V / 5.2Ah	
WORKING PRESSURE	Low Speed (open flow) 8 psi	High Speed (dead head) 115 psi	BATTERY CELL TYPE	Lithium Ion	
SEAL TYPE	Viton™		CHARGER TYPE	21V / 1A	
FLOW RATE	Low Speed (open flow) .12 GPM	High Speed (open flow) 1.12 GPM	CHARGE TIME	~1.5 hours	
LIQUID OUTPUT / CHARGE	Low Speed (open flow) > 110 gal	High Speed (open flow) > 110 gal	BATTERY CYCLE LIFE	1,000 Charge Cycles	
SPRAY DISTANCE	> 30 Feet (8 Meters)		CONTINUOUS WORKING TIME	Low Speed > 180 minutes	High Speed > 140 minutes
AGENCY/STANDARDS APPROVALS	UL / CE / RoHS				