

BAR FRIDGES

Cooling the Beers of a Nation *New Zealand*

New Zealand's best range of chillers

MODEL: SG3H-B

QUICK INFO

Rhino 3 Door Under Bench Commercial Bar Fridge. Units encompass the best brand name parts available in the world, designed by the best engineers and built by a quality long term manufacturer, to bring a reliable product to the market.

Designed specifically for Australia alfresco areas and busy hotel-pub-club businesses.

PARTS AND ENERGY INFO

- Cyclopentane foaming
- ECO controller
- German energy saving EBM fans
- LED lighting
- LOW E glass
- R600 100% ozone safe gas
- LG Compressor
- EBM German Industrial Fan
- Meanwell Transformer From Taiwan
- Philips LED Lighting (Same Factory)



SPECIFICATIONS

Capacity (litres)	330
Holds (cans)	350
Noise Level	47
Consumption	2.24Kwh/24Hrs
Unit dimensions (WxDxH)	1350 x 500 x 840
Lockable	Yes
Gross weight	98 kg


**Specifications and price of this product may change at any time

**For more information about this product please call us or visit our website.


www.rhinoequipment.eu

PRODUCT INFORMATION

SG3H-B



INFORMATION

DIMENSIONS

Ⓐ	Overall width	1350mm
Ⓑ	Overall depth	495mm
Ⓒ	Overall height - includes feet	840mm
Ⓓ	Overall depth with door open	915mm
Ⓔ	Height of hinge cap (included in height above)	N/A
Ⓕ	Internal step inside unit	190mm In & 190mm High
Ⓖ	Depth of handle (adds to depth above)	40mm
Ⓗ	Power cord location & length	1800mm
Ⓘ	Internal dimensions (WxDxH)	1270 x 380 x 680mmH

Note: Door opens maximum 5mm outside diameter

INSTALLATION & BUILDING INTO CAVITY'S

Minimum cavity size needed (WxDxH) 1370 x 600 x 850mmH
 Venting type of fridge Front Venting, Through Grill

Note: If wanting a 'cabinet door' in front of fridge door please contact us

OTHER HELPFUL INFORMATION

Height floor to bottom of door	65mm
Door size (WxH)	445 x 755mm
Feet height fully tightened	15mm
Height adjustment available on current feet	10mm
Change feet size for extra height option	30mm
Shelf Qty / Size	6 x (445mmW x 345mmD)
Wine Shelf available (Y/N)	Yes

PERFORMANCE

Cooling	Cools easily to (1oC)
Application suitability	Commercial / Alfresco / Indoor
Maximum operating ambient temperature	38oC
Outdoor official IP rating	IP22
Meps Energy Approved & Food Grade	Yes