

JDPOWER Pty Ltd www.jdpowertools.com.au CARGO LIFTER-ES/CS SERIES

Auslift Equipment Pty Ltd

Factory 2/2-4 Souffi Place, Dandenong South, 3175

T: (03) 9702 7977 | sales@auslift.com.au | www.auslift.com.au

Built for Heavy Material Lifting!



	CARGO LIFTER		ES/CS-380	ES/CS-550	ES/CS-700	ES/CS-850
	Basic Height	cm	217	217	217	217
	Lifting Height (forks up)	cm	330	498	664	816
	Lifting Height (forks down)	cm	385	553	716	871
	Load capacity - 38.5cm from boom	Kg	300	300	300	300
	Load capacity - 70.0cm from boom	Kg	300	250	200	200
	Basic dimensions (stowed)	cm	90x76	90x76	90x76	90x76
	Basic dimensions (operating)	cm	216x170	216x170	216x170	216x170
	Fork dimensions	cm	64x56	64x56	64x56	64x56
	Ground clearance (forks up)	cm	0	0	0	0
	Ground clearance (forks down)	cm	58	58	58	58
	Machine weight-ES	Kg	176	198	219	240
	Machine weight-CS	Kg	144	166	187	209
	Shipping Size	cm	117x78x231	117x78x231	117x78x231	117x78x231

(Specifications subject to change without notice)





The erfect Lifter for:

- ◆ HVAC Contractors
- ◆ Electrical Contractors
- ◆ Industial Maintenance
- ◆ Steel Frame Erection
- ◆ Facilities Maintenance

◆ ES-700 with optional pipe forks. ◆ ES-700 with standard forks



CS - series Manual Operation



Standard Fork(Part#3017008)

- ◆Come standard with each ES/CS lifter.
- ◆Load capacity 300 kg
- ♦Weight 14 kg
- ◆Dimensions 600x700x355 mm



Optional Accessory(Part#3017014)

- ◆ ipe Forks
- ◆Load capacity 300kg
- ◆Weight 16 kg
- ◆Dimensions 600x700x355 mm



Equipped with level to help operator ensure safe setup.

Electrical or Manual

- 1. Available as a owered unit with electrical motor (ES) or Manual unit (CS).
- 2. Robust, durable mast.
- 3. Safety anti-fall system on mast.
- 4. Load capacity 300kg.
- 5. One person can easily load and unload from a vehicle.
- 6. Legs fold, making it sasy to setup and manoeuvre on-site.
- 7. Steel cable and pulleys are covered for safety.
- 8. Counter-weights are not required.

