

30AM

AUSLIFT
EQUIPMENT



PUSH AROUND VERTICAL LIFT

Performance

Platform Height	9.02 m
Working Height	11.02 m
Lift Time	75 sec
Lower Time	39 sec
Platform Capacity Standard	135 kg
Stowed Length	1.32 m
Stowed Height	1.97 m
Stabiliser Footprint Length	1.89 m
Stabiliser Footprint Width	1.81 m
Standard Platform Type	Steel Rail/Alloy Floor
Overall Width	0.74 m
Standard Platform Size (W x L)	0.66 x 0.66 m
Chassis Length	1.19 m
Platform Entry Height	0.48 m

Standard Specifications

POWER SOURCE

Power Source	Battery
DC Voltage	12V
DC Power	93 Amp/hr

TYRES

GVW AC	404 kg
GVW DC	427 kg

Applications

- Facilities maintenance
- Electricians for lighting tube/globe replacements
- All maintenance work
- Factory fit outs in tight areas
- Ideal warehouse use between racking and narrow aisle areas
- Hospitals, schools and offices for suspended ceiling maintenance

Standard Features

- Work in tight and confined vertical areas
- 4 easy fit outriggers with interlock switch and tell-tale light indicating each outrigger is locked and set
- Base can be levelled on outriggers
- Dual chain vertical mast lift
- Non-marking solid tyres
- 1 x 12V DC deep cycle battery
- Removable SCR automatic battery charger for quick recharging
- Steel rails and aluminium alloy platform floor, with drop bar entry gates for ease of use
- Dual chains and timing cable on low maintenance anodised aluminium alloy mast
- Ground controls and emergency stop switch
- 12V deep cycle battery and automatic charger, removable for transport
- Manual bleed down valve at base cylinder
- Non-marking solid wheels for sensitive floor areas
- Forklift boots at front and rear, for ease of transport
- Adjustable stabilisers, set and adjustment before elevating on solid level ground. 4 red LED lights in chassis indicate that stabilisers are set



The JLG "2&5" Warranty

JLG Industries, Inc. backs its products with its exclusive "2&5" Warranty. We provide coverage on all products for two (2) full years and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specifications and/or equipment changes without prior notification. This machine meets or exceeds AS/NZS 1418.10 2011 as originally manufactured for intended applications

Distributed by:

Auslift Equipment

2/2-4 Souffi Place

Dandenong South, Vic. 3175

Telephone: 03 9702 7977

Email: sales@auslift.com.au

Website: www.auslift.com.au

AUSLIFT
EQUIPMENT