TOUCAN 10E

MAST BOOM LIFT

Performance

Platform Height 10.10 m
Working Height 8.10 m
Working Outreach 3.38 m
Up and Over Height 6.51 m
Swing (not continuous) 345 Degrees

Platform Capacity 200 kg (2 Persons indoor

and outdoor)

Jib-Overall Length 1.60 m

126° (+65°/-61°) Jib-Range Articulation Standard Platform Size (L x W) 0.70 x 0.90 m **Drive Speed Lowered** 5.5 km/h **Drive Speed Elevated** 0.75 km/m **Drive Speed Full Elevation** 0.40 km/h Turning Radius (Outside) 1.99 m Turning Radius (Inside) 0355 m Gradeability 25% Machine Weight 2,980 kg

Standard Specifications

POWER SOURCE

Electrical System 24V DC

Batteries 24V – 240A/hr Charger 24V-27A

Drive Motors Dual AC Motors

Brakes Disc

TYRES

Tyres (Non-Marking Solid) 406 x 125 mm

HYDRAULIC SYSTEM

Electric (Pump) Motor 3kW 24V DC

Hydraulic System 7.5 L





Standard Features

- Heavy Duty Steel Roller
 Mast with 345° Rotation
- Chain Slack Detection System
- 2.5° Tilt Alarm and Indicator Light
- 406 x 125 Solid Non-Marking Tyres
- Passive Pothole Protection System
- 0.99 m Wide Frame
- Lifting/Tie Down Rings
- Ground Control Selector Switch with Key Lock
- Horn

- Battery Discharge Indicator
- Hourmeter
- Drive Orientation System
- Lanyard Anchor Points
- Zenon Strobe Light
- Acoustic Alarm
- Manual Descent
 System
- Brushless AC Drive Motors
- On Board Diagnostics with Integral Display


Accessories & Options

• 8 Air Line to Platform

Platform Work Lights

AC Outlet to Platform with ELCB





JLG Industries, Inc. backs its products with its exclusive "2&5"Warranty. We provide coverage on all products for two (2) full years and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specifications and/or equipment changes without prior notification. This machine meets or exceeds AS/NZS 1418.10 2011 as originally manufactured for intended applications

Distributed by:

Auslift Equipment

2/2-4 Souffi Place

Dandenong South, Vic. 3175 Telephone: 03 9702 7977

Email: sales@auslift.com.au
Website: www.auslift.com.au
EOUIP

