

# ES1932

Electric Scissor Lift

**AUSLIFT**  
EQUIPMENT

**JLG**

## Performance

<b>Platform Height – Elevated (Indoor/Outdoor)</b>	5.8/5.8 m
<b>Platform Capacity (Indoor/Outdoor)</b>	230/230 kg
<b>Platform Capacity (Deck Extension)</b>	120 kg
<b>No. Occupants (Indoor/Outdoor)</b>	2/1
<b>Lift/Lower Time</b>	36/28 sec
<b>Maximum Drive Height</b>	Full Height
<b>Ground Bearing Pressure</b>	8.2kg/cm <sup>2</sup>
<b>Weight</b>	1,565 kg
<b>Drive Speed – Elevated</b>	0.8 km/h
<b>Drive Speed – Lowered</b>	4.8 km/h
<b>Gradeability</b>	25%
<b>Tilt Rating Side to Side (Indoor/Outdoor)</b>	1.75°/1.5°
<b>Turning Radius (Inside/Outside)</b>	0 m/1.7 m

## Standard Specifications

### Power Source

Batteries	4 x 6V 220 amp-hr
Charger	27 amp
Drive	24V DC

### Hydraulic Reservoir

Capacity	7L
Pump	Fixed Displacement Gear

### Tires

Tire Size/Type (Non-Marking) 323 x 100mm

## Standard Features

- Proportional Controls
- Battery Condition Indicator
- AC Receptacle in Platform
- All Motion Alarm
- 27 amp Multi-Function Universal Charger
- Horn
- Hourmeter
- Tilt Alarm and Light
- Lanyard Attachment Points
- Movable, Removable Control Box
- Nickel Plated Pins
- Lubrication Free Scissor Arm Bushings
- Removable Ladder
- QuikFold Rails
- Smart Charger
- USB Charger & Phone Holster
- Scissor Maintenance Prop
- Active Pothole Protection System
- Lifting and Tie Down Points
- Fork Lift Pockets
- Foot-Actuated Deck Extension
- Steel Swing Out Doors
- Variable Tilt Visual Zone Indicator
- Manual Decent Cable
- Diamond Trend Steel Deck
- Greaseless Kingpin Joints
- Analyzer Port for Diagnostics
- Dynamatic Braking
- Self-Closing Gate
- DC Electric Drive
- Telematics-Ready Harness
- Load Sensing System
- ANSI A92.20 Compliant

## Accessories & Options

- CleanGuard
- Coiled Platform Control Box Cable
- Drive Motor Covers
- Flashing Amber Beacon
- MDI (Ground)
- Anti-Vandalism PKG
- Eagle Performance Charger
- 900W Inverter
- White Noise Alarm
- JLG™ Mobile Control
- SkySense™ Level I
- QuickAccess Platform



## Dimensions

All dimensions are approximate.



Platform Height – Elevated	5.8m
A. Platform Height – Lowered	1.0m
B. Platform Railing Height	1.1m
C. Overall Height	1.63m
D. Platform Dimensions	1.59 x 0.64m
E. Platform Extension	0.91m
F. Overall Machine Length	0.81m
G. Overall Machine Width	1.7m
H. Wheelbase	1.3m
I. Ground Clearance	7cm

## The JLG “1 & 5” Warranty

We provide coverage for one (1) full year, and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds applicable ANSI and CSA requirements based on machine configuration as originally manufactured for intended applications. Please reference the serial number plate on the machine for additional information.

**AUSLIFT**  
EQUIPMENT

**Auslift Equipment Pty. Ltd.**  
Factory 2/4 Souffi Place,  
Dandenong South, Vic 3175  
T: (03) 9702 7977  
[www.auslift.com.au](http://www.auslift.com.au)