

ES2632

Electric Scissor Lift

AUSLIFT
EQUIPMENT

JLG

Performance

Platform Height – Elevated (Indoor/Outdoor)	7.8/6.4 m
Platform Capacity (Indoor/Outdoor)	230/125 kg
Platform Capacity (Deck Extension)	120 kg
No. Occupants (Indoor/Outdoor)	2/1
Lift/Lower Time	32/24 sec
Maximum Drive Height (Indoor)	Full Height
Maximum Drive Height (Outdoor)	6.4m
Ground Bearing Pressure	6.6kg/cm ²
Weight	1,996 kg
Drive Speed – Elevated	0.8 km/h
Drive Speed – Lowered	4.4 km/h
Gradeability	25%
Tilt Rating Side to Side (Indoor/Outdoor)	1.5°/1.5°
Turning Radius (Inside/Outside)	0 m/2.2 m

Standard Specifications

Power Source

Batteries	4 x 6V 220 amp-hr
Charger	27 amp
Drive	24V DC

Hydraulic Reservoir

Capacity	12L
Pump	Fixed Displacement Gear

Tires

Tire Size/Type (Non-Marking) 406 x 125mm

Dimensions

All dimensions are approximate.



Standard Features

- Proportional Controls
- Battery Condition Indicator
- AC Receptacle in Platform
- All Motion Alarm
- 27 amp Multi-Function Universal Charger
- Horn
- Hourmeter
- Tilt Alarm and Light
- Lanyard Attachment Points
- Movable, Removable Control Box
- Nickel Plated Pins
- Lubrication Free Scissor Arm Bushings
- Removable Ladder
- QuikFold Rails
- Smart Charger
- USB Charger & Phone Holster
- Scissor Maintenance Prop
- Active Pothole Protection System
- Lifting and Tie Down Points
- Fork Lift Pockets
- Foot-Actuated Deck Extension
- Steel Swing Out Doors
- Variable Tilt Visual Zone Indicator
- Manual Decent Cable
- Diamond Trend Steel Deck
- Greaseless Kingpin Joints
- Analyzer Port for Diagnostics
- Dynamatic Braking
- Self-Closing Gate
- DC Electric Drive
- Telematics-Ready Harness
- Load Sensing System
- ANSI A92.20 Compliant

Accessories & Options

- CleanGuard
- Coiled Platform Control Box Cable
- Drive Motor Covers
- Flashing Amber Beacon
- MDI (Ground)
- Anti-Vandalism PKG
- White Noise Alarm
- 900W Inverter
- Eagle Performance Charger
- JLG™ Mobile Control
- SkySense™ Level II



Platform Height – Elevated	7.8m
A. Platform Height – Lowered	1.1m
B. Platform Railing Height	1.1m
C. Overall Height	2.2m
D. Platform Dimensions	2.1 x 0.7m
E. Platform Extension	0.86m
F. Overall Machine Width	0.81m
G. Overall Machine Length	2.4m
H. Wheelbase	1.9m
I. Ground Clearance	9.8cm

The JLG “1 & 5” Warranty

We provide coverage for one (1) full year, and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds applicable ANSI and CSA requirements based on machine configuration as originally manufactured for intended applications. Please reference the serial number plate on the machine for additional information.

AUSLIFT
EQUIPMENT

Auslift Equipment Pty. Ltd.

Factory 2/4 Souffi Place,
Dandenong South, Vic 3175

T: (03) 9702 7977

www.auslift.com.au