

R4045

Electric Scissor Lift

AUSLIFT
EQUIPMENT



Performance

Platform Height – Elevated (Indoor/Outdoor)	12/8.8 m
Platform Capacity (Indoor/Outdoor)	350/250 kg
Platform Capacity (Deck Extension)	113 kg
No. Occupants (Indoor/Outdoor)	3/1
Lift/Lower Time	70/35 sec
Maximum Drive Height (Indoor)	Full Height
Maximum Drive Height (Outdoor)	8.8m
Ground Bearing Pressure	9.5 kg/cm ²
Weight	3,175 kg
Drive Speed – Elevated	0.8 km/h
Drive Speed – Lowered	3.4 km/h
Gradeability	25%
Tilt Rating Side to Side (Indoor/Outdoor)	1.5°/1.5°
Turning Radius (Inside/Outside)	0 m/2.5 m

Standard Features

- Proportional Controls
- Fold Down Rails
- Battery Condition Indicator
- AC Receptacle in Platform
- All Motion Alarm
- 27 amp Multi-Function Universal Charger
- Horn
- Hourmeter
- Tilt Alarm and Light
- Lanyard Attachment Points
- Movable, Removable Control Box
- Nickel Plated Pins
- Lubrication Free Scissor Arm Bushings
- Scissor Maintenance Prop
- Active Pothole Protection System
- Lifting and Tie Down Points
- Fork Lift Pockets
- Foot-Actuated Deck Extension
- Steel Swing Out Doors
- Variable Tilt Visual Zone Indicator
- Manual Decent Cable
- Diamond Trend Steel Deck
- Greaseless Kingpin Joints
- Analyzer Port for Diagnostics
- Dynamatic Braking
- Self-Closing Gate
- Removable Ladder

Standard Specifications

Power Source

Batteries	4 x 6V 220 amp-hr
Charger	27 amp
Drive	Hydraulic Front-Wheel

Hydraulic Reservoir

Capacity	30L
Pump	Fixed Displacement Gear

Tires


Tire Size/Type (Non-Marking) 406 x 127 mm

Brakes

Multi-Disc Function

Dimensions

All dimensions are approximate.



Accessories & Options

- Coiled Platform Control Box Cable
- Drive Motor Covers
- Flashing Amber Beacon
- MDI (Ground)
- Anti-Vandalism PKG
- Ambient Noise Alarm
- JLG™ Mobile Control
- Eagle Performance Charger
- 900W Inverter



Platform Height – Elevated	12.0m
A. Platform Height – Lowered	1.0m
B. Platform Railing Height	1.1m
C. Overall Height	2.5m
D. Overall Height (Rails Lowered)	1.9m
E. Platform Dimensions	2.4 x 1.1m
F. Platform Extension	0.91m
G. Overall Machine Width	1.14m
H. Overall Machine Length	2.7m
I. Wheelbase	2.0m
J. Ground Clearance	12.7cm

The JLG “1 & 5” Warranty

We provide coverage for one (1) full year, and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds applicable ANSI and CSA requirements based on machine configuration as originally manufactured for intended applications. Please reference the serial number plate on the machine for additional information.

AUSLIFT
EQUIPMENT

Auslift Equipment Pty. Ltd.
Factory 2/4 Souffi Place,
Dandenong South, Vic 3175
T: (03) 9702 7977
www.auslift.com.au