

Standard Features

Measurements

- 13.94 m working height
- Up to 350 kg lift capacity

Productivity

- Drive at full height
- Folding rails with full height swing gate
- SmartLink™ - dual zone control
- Proportional lift and drive
- Platform load sense system
- Platform control guard
- Platform control with battery charge indicator
- AC power to platform
- Universal 27A smart charger
- Lanyard attachment points
- Manual platform lowering valve
- Emergency stop at both platform and ground controls
- Dual front wheel AC electric drive motors (E-drive)
- Electric & manual brake release
- Swing-out component trays
- Pothole guards
- Tilt level sensor with audible alarm
- Dual flashing LED beacons
- Descent alarm
- Electronic horn
- Hour meter
- Motion alarm
- Tech Pro™ Link compatible
- Maintenance free steel diamond plate platform

Standard Features

Power

- 24 V DC, 210 Ah
- Universal 20 amp smart charger

Platform

- 2.26 x 1.15 m steel platform
- 0.19 m extension deck

Drive

- Dual front wheel AC drive (E-drive)

Tires

- Solid non-marking

Options & Accessories

Productivity Options

- Air line to platform
- Automotive-style horn
- Lift Tools™ Pipe Cradle
- Lift Tools Panel Cradle
- Lift Tools Work Tray
- Lift Guard™ Contact Alarm
- Lift Connect™ Telematics

Power Options

- Power Inverter (120 V/60Hz)¹
- Drive cutout while charging



¹ Not available with EE rating