

0808SE (2732SE)

Model		0808E (2732SE)
Dimensions		
Max Working Height		10.1m
A Max Platform Height		8.1m
B Max Horizontal Extension		0.9m
C Length-Stowed		2.46m
D Width-Stowed		0.83m
Height-Stowed	Rail Folded	1.96m
	E Fixed Rails	2.36m
F Wheelbase		1.88m
Ground Clearance (Pothole Guard Stowed)		0.1m
Ground Clearance (Pothole Guard Deployed)		25mm
Platform Dimensions (LxWxH)		2.30m x 0.8m x 1.1m
Performance		
Platform Allowable Occupants (Indoor/Outdoor)		2 Persons/1 Persons
Platform Capacity		250kg
Drive Speed-Stowed		4km/h
Drive Speed-Raised		0.8km/h
Elevation Time (Unloaded)		30s~35s
Decent Time (Unloaded)		34s~39s
Gradeability		25%
Turning Radius (Inside/Outside)		0/2.1m
Tilt Rating (Front to Back/Side to Side)		3°/1.5°
Tyres-solid		380x125mm
Power		
Batteries		12V x 4/225Ah
Power Source		24V DC
Drive Mode		Motor, front-wheel
Charger Input/Output		100~240V AC/30A
Hydraulic System Capacity		15L
Weight		
Weight (Indoor/Outdoor)		2,090kg

Standard Features

- Maintenance-free battery
- Proportional control
- Bumper rail
- 4 x 2 drive
- Non-marking tyres
- Integrated hand shield
- Automatic braking system
- Emergency lowering system
- Emergency stop (at platform & ground controls)
- Fault diagnosis system
- Tilt protection
- Automatic pothole guard
- Drive at full height
- Forklift pocket and lifting eyes
- Electrophoresic paint technology
- Foldable guardrail
- Overloading sensing system

Optional Features

- Overhead anti-collision device
- AC power to platform
- Headlight
- RCBO

