


Specifications



Models	SLC-12™		SLC-18		SLC-24	
Measurements	US	Metric	US	Metric	US	Metric
Working height:						
standard forks - forks down	11 ft 2 in	3.40 m	16 ft 9 in	5.10 m	22 ft 3 in	6.78 m
standard forks - forks up	12 ft 11 in	3.94 m	18 ft 6 in	5.64 m	24 ft	7.32 m
adjustable forks - forks down	11 ft 2 in	3.40 m	16 ft 9 in	5.10 m	22 ft 3 in	6.78 m
adjustable forks - forks up	12 ft 11 in	3.94 m	18 ft 6 in	5.64 m	24 ft	7.32 m
boom**	12 ft 2 in	3.70 m	17 ft 9 in	5.41 m	23 ft 3 in	7.10 m
A Height - stowed	7 ft 2 in	2.18 m	7 ft 2 in	2.18 m	7 ft 2 in	2.18 m
B Length - stowed	2 ft 10 in	.86 m	2 ft 10 in	.86 m	2 ft 10 in	.86 m
C - operating	5 ft 3 in	1.60 m	6 ft 1 in	1.85 m	6 ft 9 in	2.06 m
D Width - stowed*	2 ft 7.5 in	.80 m	2 ft 7.5 in	.80 m	2 ft 7.5 in	.80 m
- with stabilizers lowered	5 ft 6 in	1.68 m	5 ft 6 in	1.68 m	5 ft 6 in	1.68 m

Productivity

Load capacity:

14 in (36 cm) load center	650 lbs	295 kg	650 lbs	295 kg	650 lbs	295 kg
24 in (61 cm) load center	425 lbs	193 kg	425 lbs	193 kg	425 lbs	193 kg
42 in (107 cm) load center	180 lbs	82 kg	160 lbs	73 kg	160 lbs	73 kg
A Ground clearance	2 in	.05 m	2 in	.05 m	2 in	.05 m
Load height minimum	6 in	.15 m	6 in	.15 m	6 in	.15 m

Power

Average cranks - per length unit

Standard winch - carriage moving	12.5/ft	41/m	12.5/ft	41/m	12.5/ft	41/m
Standard winch - mast moving	5.5/ft	18/m	5.5/ft	18/m	5.5/ft	18/m

Weight

	225 lbs	102 kg	307 lbs	139 kg	347 lbs	157 kg
--	---------	--------	---------	--------	---------	--------

Load Handling Attachments

Measurements	US	Metric	Weight (US)	Weight (Metric)
Standard forks assembly (l/w/d)***	28/23/2.5 in	71/58/6 cm	26.5 lbs.	12 kg
Standard fork size (each)	2.5/1.5 in	6/4 cm		
Adjustable forks assembly (l/w/d)***	27.5/11-30/2.5 in	70/28-76/6 cm	52.5 lbs.	24 kg
Adjustable fork size max (each)	3.0/1.5 in	7/4 cm		
Fork extensions detached (each) (l/w/d)***	30/2/3 in	76/5/8 cm	4.5 lbs	2 kg
Fork extension attached (each) (l/w/d)***	35/2/3 in	64/5/8 cm	4.5 lbs	2 kg
Boom (l/w/d)***	18,24,32,44/1.5/6 in	46,61,81,112/4/15 cm	39.9 lbs	18 kg
Load platform (l/w/d)***	26.3/23/2.5 in	67/58/6 cm	23.8 lbs	11 kg

* Outside dimensions.

** Measured from ground to bottom of shackle.

*** Length/Width/Depth, from end of carriage and outside of forks

Features

Standard Features

Measurements

SLC™ -12

- 12 ft 11 in (3.94 m) maximum lifting height
- Up to 650 lbs (295 kg) lift capacity

SLC-18

- 18 ft 6 in (5.64 m) maximum lifting height
- Up to 650 lbs (295 kg) lift capacity

SLC-24

- 24 ft (7.32 m) maximum lifting height
- Up to 650 lbs (295 kg) lift capacity

Productivity

- Standard forks
- Heavy-duty design
- Strong, lightweight aluminum telescoping mast
- Single door access
- Quick set up requires no tools
- Interchangeable load handling attachments
- Non-marking 4 in (10 cm) front casters and 5 in (13 cm) rear casters with side brakes
- Rear transport wheel assembly
- Glide rails allow easy loading and unloading, on or off a vehicle, for transport
- Hold-down bar secures mast assembly during transport
- Captive stabilizer set (standard on SLC™ -18, -24)
- Winch locks load in place

Power

- One speed manual winch

Options & Accessories

Productivity & Platform Options

- Boom
- Adjustable forks
- Fork extensions
- Pipe cradle (available aftermarket only)
- Load platform
- Mast Brake

Power Options

- Two speed manual winch (available on SLC™ -18, -24)

Base Options

- Standard base
- Stabilizer set (available on



Genie United States

6464 185th Ave. NE
Redmond, WA 98052
Telephone +1 (425) 881-1800
Toll Free in USA/Canada +1 (800)-536-1800
Fax +1 (425) 883-3475

Distributed By:

Auslift Equipment Pty Ltd
2/2-4 Souffi Pl, Dandenong South
Vic. 3175
Phone: (03)9702 7977
Email: sales@auslift.com.au