

# WEE-1200 AirEEG

Spezifikationen auf einen Blick

Juni 2017  
NIHON KOHDEN Deutschland GmbH  
Marketing

**Inputs:  
JE-922A**

- EEG: 25ch (max.)
- Bipolar: 7ch (7pairs)
- DC: 2ch
- SpO2: 1ch

**Inputs:  
JE-125AK**

- EEG: 64ch (max.)
- Bipolar: 4ch (4pairs)
- DC: 2ch
- SpO2: 1ch

**Sampling Frequency**

- 4k, 2k, 1k, 500, 200Hz
- 4kHz/32ch or 2kHz/64ch

**Filter**

- High cut: 1200Hz(max.)
- Low cut: 0.08Hz(max.) (TC 2s)

**Input Impedance**

- 200M $\Omega$
- $\pm 3.2\text{mV} / \pm 12.8\text{mV}$

**Internal Noise Level**

- 1.5 $\mu\text{Vp-p}$  or less (<60Hz)
- 2.1 $\mu\text{Vp-p}$  or less(<120Hz)

**CMRR**

- 105dB or more

**Electrode offset  
potential tolerance**

- $\pm 1000\text{mV}$

**Wireless/Security**

- IEEE802.11 a/b/g/n
- 2.4GHz
- 5GHz
- WEP, WPA, WPA2

**Network**

- Fixed IP address
- DHCP address (Future)
- DNS (Future)

**Dimesion/Weight**

- 130x130x41mm (WxHxD)
- 560g (including battery)



Improving Healthcare with Advanced Technology

**Nihon Kohden 2017**