

# ALTRACK

## LED Track Light

Norms: EN 60598-1, EN 60598-2-1, EN 62471, EN 62493



### Product information



Product number:	ALT70 - L20
Track System:	2 wire, 4 wire
Input Voltage (v):	48VDC
Dimming:	On/Off, 1-10V, DALI
Light source:	COB LED
luminaire Lifetime:	50.000h (L80-B10, Ta25°C)
Rotation Angle (degree):	350
Tilting Angle (degree):	60
IP Rating:	20
Working Temperature (°C)	-5 - +30
Storage Temperature (°C)	-20 - +50
Material:	Aluminium
Fitting Colors:	9016 Matte White / 9017 Matte Black




### Packaging information

N.W. lamp (Kg):	0.6
G.W. Carton (Kg):	12
Master carton dimensions(mm):	430x430x390
Quantity per carton:	16



Honeycomb L01    Oval diffuser L02    Diffuser L03    Anti-glare ring L04

Beam	Watt	CRI	Luminous	CCT	Code
16	20W	90	1820.0 lm	4000K	JALT704-L20G40-S
			1717.0 lm	3000K	JALT704-L20G30-S
			1596.8 lm	2700K	JALT704-L20G27-S
22	20W	90	1809.4 lm	4000K	JALT704-L20G40-M
			1707.0 lm	3000K	JALT704-L20G30-M
			1587.5 lm	2700K	JALT704-L20G27-M
34	20W	90	1679.2 lm	4000K	JALT704-L20G40-F
			1584.2 lm	3000K	JALT704-L20G30-F
			1473.3 lm	2700K	JALT704-L20G27-F
43	20W	90	1644.7 lm	4000K	JALT704-L20G40-WF
			1551.6 lm	3000K	JALT704-L20G30-WF
			1443.0 lm	2700K	JALT704-L20G27-WF



Code composition: ALT 85 6 - D 40 G27 - B S - L01

① Product Code	② Diameter size	③ Track style	④ Dimming type	⑤ Watt	⑥ LED K & CRI	⑦ Finishes	⑧ Optical angle	⑨ Accessories
JALT	φ 85mm	6 Wire	X Not-Driver	40W	H27 2700 95	White	S Spot M	L01 Honeycomb
	φ 70mm	4 Wire	T TRIAC	37W	G27 2700 90	Black	Medium F	L02 Oval diffuser
	φ 55mm	3 Wire	V 1-10V	35W	G30 3000 90		Flood	L03 Diffuser
	φ 45mm	2 Wire	D DALI	32W	G40 4000 90		WF Wide Flood	L04 Anti-glare ring
	φ 35mm		L DC48V		E50 5000 80		O Oval	