




LIGNUM RETAIL SERIES

MACELLUM



ماجاز

LIGNUM RETAIL SERIES MACELLUM




ABOUT

THE MACELLUM SERIES IS HIGHLY VERSATILE

The Macellum 2.0 series is highly versatile: different lens optics (30°, 60°, 90°, 110°, double asymmetric and single asymmetric is optional) combined and the track-mounted variant can be rotated. It can meet the needs in conventional general lighting, also, the Macellum 2.0 is suitable for places with special light distribution requirements, such as shelf and aisles lighting.


The series is simple and compact, suitable for European standard three-circuit track system, which is convenient for group control management. At the same time, it has multiple smart control option, such as DALI dimming, 1-10V dimming, 2.4G wireless dimming, etc.

LIGNUM RETAIL SERIES MACELLUM



KEY FEATURES

Universal track adapter design, compatible with multiple-brands European 3 circuits track. A variety of light distribution angles are available to meet different application needs. The luminaire can be rotated through $\pm 350^\circ$






DETAILS

Power: 40W / 60W / 75W
LEDs: SMD2835
CCT: 3000K, 4000K, 5000K, Meat,
Fruits, Bread Ra >80 / >90
Light Efficiency: Upto 145lm/w
Driver: Osram
Input Voltage: AC200-240V
Material: Aluminum
Surface Treatment: Powder-Coated

Finish Color: Black / White
Beam Angle: 30/60/90/Single & Double
Asymmetric Dimming: 1-10V, DALI, RF-2.4G
Adaptor: 3 Circuits / Phases
IP Grade: IP20
Net Weight: 2.3Kg
Product Size: 580*190*116mm
Warranty: 5 Years

**LIGNUM RETAIL SERIES
MACELLUM**



350 DEGREES ROTATION


System wattage / luminous fluxes can be adjusted.

Different lens optics (30°/ 60°/ 90°/ Single & Double asymmetric is optional) combined.


The track-mounted can be 350°rotated. It can meet the needs in conventional general lighting,

It is also suitable for places with special light distribution requirements, such as shelf and aisles lighting.

LIGNUM RETAIL SERIES MACELLUM



3 CIRCUITS RAILS



COMPATIBLE WITH:

- GLOBAL
- NORDIC
- STAFF
- EUTRAC
- NUCO
- IVELA
- POWERGEAR

LIGNUM RETAIL SERIES MACELLUM



SMART CONTROL:

- RF 2.4G Dimming
- 1-10V Dimming
- DALI Dimming

SPECIAL LED'S FOR:

- Meat
- Fish
- Fruits
- Bread





Cylinder series

LTA-X-6-3-75-8-DA

UGR<19


Technical Parameters:

Name	Parameters
Light source:	SMD
Input Voltage:	AC220~240V 50/60Hz
LED Current:	375mA
Beam Angle:	36°/70°/90°/single/double assymmetric
Life Time:	> 50,000h - L80 - B50 (Ta 25° C)
Operating temperature:	-20°C~40°C
Certificate:	CE/RoHS
Weight:	3.0kg



Ordering Information:

○White ● Black




Power	CRI	Beam Angle	Luminous	CCT	Housing	Part Number
75W	>80	 DA	9354lm	3000K	●	JLTA-06-3000K
			9454lm	4000K	●	JLTA-06-4000K

Technical Data test pattern


CRI80 36°

3000K


4000K




CRI80 70°




3000K




4000K




CRI80 90°




3000K




4000K




CRI80 SA




3000K




4000K




CRI80 DA






3000K




4000K





Packaging:



Outer carton:
 L645*W541*H400mm
 6pcs/CTN
 GW: 20.5kg/carton

JIBE LIGHTING – HEADQUARTERS
Hogebrinkerweg 14V - 3871 KN Hoevelaken
Netherlands Tel: +31 (0)33 844 7111
info@jibe.lighting - www.jibe.lighting



LED THERE BE LIGHT

© 2019 Jibe Lighting - all rights reserved

Jibe reserves the right to alter material, dimensions and characteristics without prior notice.

Read installation instructions carefully. Technical information on the installation instruction has precedence over the information in the brochure.

Our general terms and conditions shall apply notwithstanding any stipulation to the contrary to all the orders and agreements with Jibe.

You can obtain a copy of these conditions on demand.

For latest information and specifications of the full product range visit www.jibe.lighting