

ALTRACK

LED Track Light

Norms: EN 60598-1, EN 60598-2-1, EN 62471, EN 62493

Product information



Product number:	2X-ALT35 - L06
Track System:	2 wire, 4 wire
Input Voltage (v):	48VDC
Dimming:	On/Off, 1-10V, DALI
Light source:	COB LED
luminaire Lifetime:	50.000h (L80-B10, Ta25°C)
Rotation Angle (degree):	350
Tilting Angle (degree):	60
IP Rating:	20
Working Temperature (°C)	-5 - +30
Storage Temperature (°C)	-20 - +50
Material:	Aluminium
Fitting Colors:	9016 Matte White / 9017 Matte Black




Packaging information

N.W. lamp (Kg):	0.2
G.W. Carton (Kg):	16
Master carton dimensions(mm):	450x360x300
Quantity per carton:	40



Honeycomb Oval diffuser Diffuser
L01 L02 L03

Beam	Watt	CRI	Luminous	CCT	Code
16	12W	90	1098.2 lm	4000K	2X-JALT352-L06G40-S
			1036.2 lm	3000K	2X-JALT352-L06G30-S
			963.6 lm	2700K	2X-JALT352-L06G27-S
24	12W	90	1042.8 lm	4000K	2X-JALT352-L06G40-M
			983.8 lm	3000K	2X-JALT352-L06G30-M
			915.0 lm	2700K	2X-JALT352-L06G27-M
34	12W	90	1048.0 lm	4000K	2X-JALT352-L06G40-F
			988.8 lm	3000K	2X-JALT352-L06G30-F
			919.6 lm	2700K	2X-JALT352-L06G27-F



Code composition: ALT 85 6 - D 40 G27 - B S - L01

① Product Code	② Diameter size	③ Track style	④ Dimming type	⑤ Watt	⑥ LED K & CRI	⑦ Finishes	⑧ Optical angle	⑨ Accessories
JALT	Φ 85mm	6 Wire	X Not-Driver	40W	H27 2700	95 White	S Spot M	L01 Honeycomb
	Φ 70mm	4 Wire	T TRIAC	37W	G27 2700	90 Black	Medium F	L02 Oval diffuser
	Φ 55mm	3 Wire	V 1-10V	35W	G30 3000	90	Flood	L03 Diffuser
	Φ 45mm	2 Wire	D DALI	32W	G40 4000	90	WF Wide Flood	L04 Anti-glare ring O
	Φ 35mm		L DC48V		E50 5000	80	Oval	