

EDGE II

Recessed Downlight

Norms: EN 60598-1, EN 60598-2-1, EN60598-2-2

Product information



Product number:	REG2055F - 8W
Input Voltage (v):	220-240V
Dimming:	On/Off, TRIAC, 1-10V, DALI
Light source:	COB LED
luminaire Lifetime:	50.000h (L80-B10, Ta25°C)
Rotation Angle (degree):	350
Tilting Angle (degree):	N/A
IP Rating:	20
Working Temperature (°C)	-5 ~ +30
Storage Temperature (°C)	-20 ~ +50
Material:	Aluminium
Fitting Colors:	9016 Sandy White / 9017 Sandy Black



Square Trim




Square Trimless

Packaging information

N.W. lamp (Kg)	0.24
G.W. Carton (Kg)	18
Master carton dimensions(mm)	655x620x225
Quantity per carton(PCS)	60

Beam	Watt	CRI	Luminous	CCT	Code
20	8W	90	558.8	4000K	REG2055FS-08G40
			494.6	3000K	REG2055FS-08G30
			460.0	2700K	REG2055FS-08G27
30	8W	90	626.1	4000K	REG2055FM-08G40
			541.2	3000K	REG2055FM-08G30
			503.3	2700K	REG2055FM-08G27
40	8W	90	644.6	4000K	REG2055FF-08G40
			571.8	3000K	REG2055FF-08G30
			531.8	2700K	REG2055FF-08G27



Code composition: REG2 055 F R1 W - R S 01 - D 08 G27

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩ ⑪

Product Code	Hole Cut Size	Structural	Structural style	Finishes	Optical	Angle	Anti-glare cover	Dimming	Watt	LED	Kelvin & CRI
REG2	Φ55mm	Fixed	R1	Round Trim	White	Reflector	S Spot	01 Mirror silver	X Not-Driver	8W	H27 2700 95
			Adjustable	R2	Round Trimless	Black	Lens	M Medium	02 Flax Silver	T TRIAC	G27 2700 90
	Wall Washer	S1	Square Trim	S2	Square Trimless		F Flood	03	Matte white	V 1-10V	G30 3000 90
								04	Blinding black	D DALI	G40 4000 90
								05	Bright black		E50 5000 80
								06	Matte black		
								07	Charm Gold		