

100% Acrylic Latex Paint

Madison Paint is a 100% Acrylic Latex Paint that contains high solids and gives excellent coverage. It is a very low odor paint that sprays on smooth and is easy to touch up. Madison Paint is self priming and has very good adhesion. It provides early water resistance and will adhere to both chalky and weathered surfaces, and won't flake or peel. You can expect consistent colors.

For use on wood, concrete blocks, pre-primed metal, primed siding, cement board, storage sheds, barns and houses.





3311 - SK White	3341 - SK Navajo White	3307 - SK Stoltzfus Beige
3363 - SK Lantz Almond	3373 - Satin SK Better Almond	3367 - Satin Elite Tan
3327 - Satin SK Clay	3333 - Satin Buckskin	3347 - Satin Chestnyt
3351 - Satin Chestnut Brown	3357 - Satin Charcoal Brown	3305 - Satin Millcreek Green
3365 - Satin Avocado	3375 - Satin Dark Green	3385 - Satin Lanco Green
3304 - Satin Ocean Blue	3348 - Satin Cape Cod Gray	3314 - Satin Wedgewood Blue
3321 - Satin Belmont Blue	3368 - Satin Dawn Gray	3356 - Satin Barn Red
3346 - Satin New Barn Red	3377 - Satin Quaker Tan	3313 - Satin New Holland Beige
3326 - Satin Stauffer Red	+ Custom Colors	

available in 1^{QT} , 1^{GAL} , 5^{GAL} & 55^{GAL} drum.

Application Instructions

Stir/Mix thoroughly before using. Apply using either a brush, roller or airless sprayer. When spraying a #517 tip is recommended. For best results two coats are recommended on previously unpainted surfaces. Allow the first coat to dry before applying a second coat.

Ideal application temperature is between 45° F and 85° F. Do not use outside in temperatures of 35°F or lower or in direct sunlight on a hot day. Also avoid using outside in late afternoon or evening when there is a chance of moisture collecting on the wet film and preventing it from drying, or when there is a chance of rain.

