



Input Voltage



Moisture ✓
Salt spray ✓
Corrosion ✓



MCU control system



Generator friendly

Stealth

IMachines

9021H Digi-Arc 175 LT

230V

FEATURES

- Digital display
- Built-in hot start, anti sticking and arc force
- Lift/Tig facility
- Carry case can be supplied as an optional extra (9029)



SPECIFICATIONS

Input power voltage (V)	230±10%	
Frequency (Hz)	50/60	
	MMA	TIG
Effective input current (A)	17	24
Maximum (KVA)	8.5	
Current adjustment range (A)	10-160	
Maximum no-load voltage (V)	62	
Duty cycle (A) (40°C 10 min)	40% @ 160	
	60% @ 135	
	100% @ 105	
Efficiency (%)	≤80	
Protection class	Ip23	
Insulation class	H	
Cooling	Air	
Electrode diameter (mm)	1.6-4.0	
Electrode type	6013, 7018, etc	
Overall dimensions (mm)	362 x 148 x 280	
Weight (kg)	4.5	
Accessories included	3m earth return lead, 3m electrode lead	

ACCESSORY KIT

9806

Scratch Start Tig Package consisting of:

- ET17V-12 Torch
- WP17AK Accessory Kit
- D3595-1-3MT Extended Tig Adaptor