

DATA SHEET

Picomig 220 puls TKG

090-005680-00502



- Multiprocess MIG/MAG pulse welding machine, compact, portable, Euro torch connector, with PFC module, for 5 kg D200 spools
- High-efficiency current draw thanks to integrated PFC (Power Factor Correction) technology
- **Welding procedures and functions**
- GMAW pulsed welding and GMAW standard welding
- Significantly less spatter formation and therefore less finishing work, all thanks to the pulse function
- GMAW pulse welding of aluminium and aluminium alloys
- Characteristics for steel, CrNi, CuSi, aluminium and flux cored wires
- MMA welding and TIG lift arc welding
- Perfect for welding self-shielding flux cored wires
- Infinitely adjustable arc dynamics (choke effect)
- Non-latched/latched operation
- Interval welding
- Adjustable gas pre- and post-flow time
- **Your benefits**
- Portable, compact
- **all in** No need to purchase additional characteristics – all characteristics for this machine type are included in the scope of delivery ex works
- Robust casing suitable for construction site use
- High open circuit voltage for excellent ignition characteristics
- 4-roll drive
- Energy-saving thanks to high efficiency and standby function
- Easy, tool-free change of welding polarity
- Insulated wire space
- 3.5 m mains supply lead with 16 A shock-proof plug
- Free WPQR package for certification up to and including EXC2 in accordance with EN 1090 and for welding of unalloyed steels up to and including S355
- **Overvoltage protection: No damage to machine caused if inadvertently connected to 400-V mains voltage**

Version	Picomig 220 puls TKG
Setting range for welding current	5 A - 220 A
Duty cycle 40 °C	220 A / 30 % 170 A / 60 % 150 A / 100 %
Open circuit voltage	70 V
Netztoleranzen (ab Werk)	-40 % up to +15 %
Mains frequency	50 Hz / 60 Hz
Recommended generator power	8.8 kVA
Power consumption Pi	15 W
Factory-installed roll equipment	0.8 + 1.0 mm / Steel
Spool diameter	D200
Torch connection	Euro torch connector
Protection classification	IP23
Test mark	CE UK EAC S
EMC class	A
Dimensions (L x B x H)	559 mm x 276 mm x 340 mm 22 inch x 10.9 inch x 13.4 inch
Weight	18 kg / 39.7 lbs
Standards	IEC 60974-1, -5 and -10 CL.A