

MinarcTig 250



TECHNICAL SPECIFICATIONS

MinarcTig 250

Product code	MinarcTig 250, TX 165GF 4M – P0607TX MinarcTig 250, TX 165GF 8M – P0608TX MinarcTig 250, TX 225G 4M – P0609TX MinarcTig 250, TX 225G 8M – P0610TX MinarcTig 250, TX 165GS 4M – P0625TX MinarcTig 250, TX 165GS 8M – P0626TX MinarcTig 250, TX 225GS 4M – P0632TX MinarcTig 250, TX 225GS 8M – P0633TX MinarcTig 250, TX 135GF 4M – P0636TX MinarcTig 250, TX 135GF 8M – P0637TX MinarcTig 250, TX 165GS 16M – P0668TX
Connection voltage 3~ 50/60 Hz	400 V (-20...+15 %)
Fuse (delayed)	10 A
Output (TIG) 30% ED	250 A/20.1 V
Output (TIG) 100% ED	160 A/16.4 V
Output (MMA) 35% ED	220 A/ 28.8 V
Output (MMA) 100% ED	150 A/26.0 V
Open circuit voltage	95 V (VRD 30 V)
Stick electrode sizes	1.5...5.0 mm
Welding range (MMA)	10 A/20.4 V - 220 A/28.8 V
Welding range (TIG)	5 A/10.2 V - 250 A/20.1 V
Operating temperature range	-20 ... +40 °C
External dimensions LxWxH	400 × 180 × 340 mm
Weight (no accessories)	11 kg (without cables)
Degree of protection	IP23S