


- Material : High Quality Polyamide 6
- Construction : Inside & Outside Corrugated Plastic Hose
- Degrees of Protection : IP 68 acc. EN 60529
- Temperature : -40°C ~ +105°C
- Short Term : +150°C
- Self-Extinguishing : UL94-VO
- Color : Black & Gray / Light gray
- Connections : CPSFIX
- Application : Machinery, Automobile, Offshore Plant, Railroad cars
- International Specification :




Product Size

• Standard Pitch : Excellent Pull-out Performance

Black	Gray	Ultraviolet Block UV-R	Inner Diameter (D1)	Outer Diameter (D2)	Bending Radius(R) mm±10%	Packing meter / roll
PAH-07B	PAH-07G	PAH-07U	6.4	10.0	15.0	50/100
PAH-10B	PAH-10G	PAH-10U	9.6	13.0	20.0	50
PAH-12B	PAH-12G	PAH-12U	11.8	15.8	30.0	50
PAH-16B	PAH-16G	PAH-16U	15.9	21.2	40.0	50
PAH-22B	PAH-22G	PAH-22U	21.7	28.5	45.0	50
PAH-28B	PAH-28G	PAH-28U	27.8	34.5	55.0	50
PAH-36B	PAH-36G	PAH-36U	36.0	42.5	60.0	30
PAH-48B	PAH-48G	PAH-48U	46.5	54.5	70.0	30
PAH-56B	PAH-56G	PAH-56U	56.3	67.2	110.0	30
PAH-70B	PAH-70G	PAH-70U	70.0	82.5	160.0	10
PAH-95B	PAH-95G	PAH-95U	91.5	106.0	210.0	10

※ Available in Light Gray(LG) production, PAHS Type can be produced



• Narrow Pitch(T) : Excellent Flexibility Performance

PAHT-22B	PAHT-22G	PAHT-22U	21.7	28.5	45.0	50
PAHT-28B	PAHT-28G	PAHT-28U	27.8	34.5	55.0	50
PAHT-36B	PAHT-36G	PAHT-36U	36.0	42.5	60.0	30
PAHT-48B	PAHT-48G	PAHT-48U	46.5	54.5	70.0	30

※ VDE Certification Excluded