


# Zubehör / Accessories

## wege® K Blindstopfen rund / Plugs round

<b>Material</b>	PA 6 GF
<b>Farbe</b>	lichtgrau (RAL 7035)
<b>O-Ring</b>	NBR-Oz
<b>Schutzklasse</b>	IP66/ IP68 – 5 bar/ IP69k
<b>Temperaturbereich</b>	-30 °C bis +100 °C

<b>material</b>	PA 6 GF
<b>colour</b>	light grey (RAL 7035)
<b>o-ring</b>	NBR-Oz
<b>protection class</b>	IP66/ IP68 – 5 bar/ IP69k
<b>range of temperature</b>	-30 °C to +100 °C


Gewinde thread	D	H	L		Bestell-Nr. ref.-number
M 12 x 1,5	17	3	6	100	775.1200.0
M 16 x 1,5	22	4	6	100	775.1600.0
M 20 x 1,5	25,5	4	6	100	775.2000.0
M 25 x 1,5	31	4,5	7	100	775.2500.0
M 32 x 1,5	37	4,5	8	100	775.3200.0
M 40 x 1,5	46	3,5	9	50	775.4000.0
M 50 x 1,5	60	5	10	25	775.5000.0
M 63 x 1,5	75	6	12	25	775.6300.0



## wege® K Blindstopfen rund / Plugs round

<b>Material</b>	PA 6 GF
<b>Farbe</b>	tiefschwarz (RAL 9005)
<b>O-Ring</b>	NBR-Oz
<b>Schutzklasse</b>	IP66/ IP68 – 5 bar/ IP69k
<b>Temperaturbereich</b>	-30 °C bis +100 °C

<b>material</b>	PA 6 GF
<b>colour</b>	jet black (RAL 9005)
<b>o-ring</b>	NBR-Oz
<b>protection class</b>	IP66/ IP68 – 5 bar/ IP69k
<b>range of temperature</b>	-30 °C to +100 °C

Gewinde thread	D	H	L		Bestell-Nr. ref.-number
M 12 x 1,5	17	3	6	100	775.1200.3
M 16 x 1,5	22	4	6	100	775.1600.3
M 20 x 1,5	25,5	4	6	100	775.2000.3
M 25 x 1,5	31	4,5	7	100	775.2500.3
M 32 x 1,5	37	4,5	8	100	775.3200.3
M 40 x 1,5	46	3,5	9	50	775.4000.3
M 50 x 1,5	60	5	10	25	775.5000.3
M 63 x 1,5	75	6	12	25	775.6300.3

