


- Material : High Quality Polyamide 12
- Construction : Inside & Outside Corrugated Plastic Hose
- Degrees of Protection : IP 68
- Temperature : -40°C ~ +105°C
- Short Term : +130°C
- Self-Extinguishing : UL94-V2
- Color : Black, Yellow
- Connections : CPSFIX
- Application : High Speed Machine, Industrial Robot
- International Specification : RoHs2, CE


## Product Size

• Standard Pitch : Excellent Pull-out Performance



Black	Yellow	Ultraviolet Block UV-R (Only Black)	Inner Diameter (D1)	Outer Diameter (D2)	Bending Radius(R) mm ± 10%	Packing meter / roll
PAR-07B	PAR-07Y	PAR-07U	6.4	10.0	15.0	50/100
PAR-10B	PAR-10Y	PAR-10U	9.6	13.0	20.0	50
PAR-12B	PAR-12Y	PAR-12U	11.8	15.8	30.0	50
PAR-16B	PAR-16Y	PAR-16U	15.9	21.2	40.0	50
PAR-22B	PAR-22Y	PAR-22U	21.7	28.5	45.0	50
PAR-28B	PAR-28Y	PAR-28U	27.8	34.5	55.0	50
PAR-36B	PAR-36Y	PAR-36U	36.0	42.5	60.0	30
PAR-48B	PAR-48Y	PAR-48U	46.5	54.5	70.0	30
PAR-56B	PAR-56Y	PAR-56U	56.3	67.2	110.0	30
PAR-70B	PAR-70Y	PAR-70U	70.0	82.5	160.0	10
PAR-95B	PAR-95Y	PAR-95U	91.5	106.0	210.0	10

• Narrow Pitch(T) : Excellent Flexibility Performance



PART-22B	PART-22G	PART-22U	21.7	28.5	45.0	50
PART-28B	PART-28G	PART-28U	27.8	34.5	55.0	50
PART-36B	PART-36G	PART-36U	36.0	42.5	60.0	30
PART-48B	PART-48G	PART-48U	46.5	54.5	70.0	30