

SOPRASOLIN HD

 TECHNICAL DATA SHEET
 030701CAN10E
 (supersedes 001218CAN12E)

DESCRIPTION

SOPRASOLIN HD is a multi-purpose self-adhesive membrane composed of SBS modified bitumen, self-protected by an aluminium sheet. **SOPRASOLIN HD** is especially designed to waterproof details around vents, chimneys, skylights, ventilation units, etc. **SOPRASOLIN HD** is recommended for repair work and all general maintenance work. **SOPRASOLIN HD** is designed to be left exposed.

INSTALLATION

1. Clean and dry the substrate.
2. Spread **ELASTOCOL STICK** primer and let dry.
3. Unroll, position and cut or shape the membrane to needed dimensions.
4. Pull out the silicone-coated film for 20 to 30 cm, and then adhere that portion on the substrate. Pull out the paper and stick the membrane.
5. Immediately after the installation, press the membrane firmly with a roller, to avoid any air pockets.

PROPERTIES

Properties	Standards	SOPRASOLIN HD
Thickness	-	1.0 mm
Dimension	-	1 x 10* m
Colour	-	Aluminium
Top face	-	Aluminium sheet
Underface	-	Silicone release sheet
Breaking strength, MD/XD	CAN/CGSB-37.56-M 9 th draft	4.7 / 4.7 kN/m
Ultimate elongation, MD/XD	CAN/CGSB-37.56-M 9 th draft	210 / 210 %
Tear resistance, MD/XD	CAN/CGSB-37.56-M 9 th draft	20 / 35 N

* Cut rolls are available upon request.
 (All values are nominal)