

# PowerWool<sup>TM</sup>

## CURTAINBOARD<sup>TM</sup>

### Physical Properties Data Sheet

**PowerWool<sup>TM</sup> CurtainBoard<sup>TM</sup>** is a semi-rigid, exterior mineral wool insulation material for increased fire protection in curtain walls systems.



Approved for use  
in Canada

CHARACTERISTIC	RESULT	TEST STANDARD	
Compliance	Mineral Fiber Thermal Insulation for Buildings - Type 1 Compliant	CAN/ULC S702	
Reaction to Fire	Flame spread index = 0; Smoke developed index = 0 Flame spread index = 0; Smoke developed index = 0 Determination of Non Combustibility of Building Materials - Non Combustible Behaviour of materials at 750°C - Non Combustible	ASTM E84 (UL 723) CAN/ULC S102 CAN/ULC S114 ASTM E136	
Density	4.5 lbs/ft <sup>3</sup> (72 kg/m <sup>3</sup> )	CAN/ULC S702.1	
Dimensional Stability	Linear Shrinkage = Pass @1200°F (650°C)	ASTM C356	
Corrosion Resistance	Stress Corrosion Cracking Tendency of Austenitic Stainless Steel - Passed Corrosion of Steel - Passed	ASTM C795 ASTM C665	
Thermal Resistance	R-Value / inch @ 75°F RSI value / 25.4 mm @ 24°C	4.2 hr.ft <sup>2</sup> .F/Btu 0.74 m <sup>2</sup> K/W	ASTM C518
Reaction to Moisture	Moisture Sorption - Pass Water Vapor Transmission, Desiccant Method - 1670ng/Pa.s.m <sup>2</sup> (29 perm) Determination of Fungi Resistance - Passed	ASTM C1104 ASTM E96 ASTM C1338	
Dimensions	1" (25.4 mm) to 6" (152.4 mm) in 1/2" increments 24" x 48" (610 mm x 1219 mm)		

\* Like most exterior rigid insulations, thermal values may decrease up to 1% per inch of thickness.

EVALUATED TO:			
CAN/ULC S701.1-14(2019)	Type 1 Compliant	ASTM C1338	Does not support fungi growth.
CAN/ULC S102	FSI: 0 SDI: 0	ASTM E84	FSI: 0 SDI: 0
CAN/ULC S114	Classified Non-Combustible	ASTM E136	Classified Non-Combustible



For exterior use only.  
Not for interior walls.

PowerWool Insulation Inc. has no control over the workmanship, design of installation, accessories used with or conditions of application, and as such we do not warranty the performance or results of any installation containing PowerWool Insulation Inc.'s products.

All information on this technical data sheet is based on data considered to be accurate, tested in laboratories and is published for the user's investigation, consideration, and verification only. Nothing written herein represents a warranty or guarantee for which the manufacturer or distributor may be held responsible legally. No responsibility for assumptions or misrepresentation is assumed by the publisher.