

POWER SILL

SILL GASKET

Product Information



Key Product Features

- Helps seal all joints and junctions between the structural components
- Fills the gap between the sill plate and foundation wall
- Helps stop heat loss
- Moisture resistant
- Easy to install
- Vapor tight

Product Specifications

- Available in 3 sizes
 - 3.5" x 75'
 - 5.5" x 75'
 - 7.5" x 75'

Contact us for more information on this or other PowerHouse Building Solutions products.

Property	Average Result
Nominal Density	1.38 lb/ft ³ (22.2kg/m ³)
Compressive Strength @ 30% Deformation, psi	2.4 psi (16.7 kPa)
Temperature Resistance (24 hours) <ul style="list-style-type: none"> • - 40°C for 24 hours • 70°C for 24 hours 	No visual changes No visual changes
Dimensional Change <ul style="list-style-type: none"> • Length • Width • Thickness 	0.2% - 0.2% 1.9%
<ul style="list-style-type: none"> • Length • Width • Thickness 	- 2.5% 1.8% - 0.1%
Tensile Strength <ul style="list-style-type: none"> • Machine Direction • Cross Direction 	70.7 psi (487.8 kPa) 37.0 psi (255.3 kPa)
Elongation <ul style="list-style-type: none"> • Machine Direction • Cross Direction 	95.1% 90.3%
24 Hour Water Absorption	0.2% by volume
Vapour Permeance	1.5 g/day-m ² (0.21 perms)
Guage Thickness	3.12mm