



Ready-Mix Joint Compounds

Safety Data Sheet

Revision date: 05/31/2017

Version: 2.0

SECTION 1: Identification

1.1. Product identifier:

Ready-Mixed Drywall Joint Compounds

Quick Identifier – Common Name (on label)	Packaging	Product Code
Red Line – Loading and Finishing Compound	17 Litre carton	895900000225
Topping – Finishing Compound	18 Litre pail	895900000201
Topping – Finishing Compound	17 Litre carton	895900000164
Taping – Joint Compound	18 Litre pail	895900000188
Taping – Joint Compound	17 Litre carton	895900000140
All Purpose – Joint Compound	18 Litre pail	895900000195
All Purpose – Joint Compound	17 Litre carton	895900000157
All Purpose – Joint Compound	3.5 Litre pail	895900000249
All Purpose – Joint Compound	0.83 Litre pail	895900000393

1.2. Recommended uses:

Drywall joint compound for finishing and repair

Restrictions on use: None known

1.3. Supplier:

Hamilton Drywall Products Canada
655 West Kent Avenue North, Unit 500
Vancouver, BC, V6P 6T7
Phone: (604) 515-0630 Fax: (604) 515-9951
www.hamiltonnw.com

Hamilton Drywall Products
295 N. Pekin Road
Woodland, WA
98674
Phone: 1-800-871-4998 Fax: 1-800-871-5007

1.4. Emergency telephone number:

Chemtrec: 1-800-424-9300

SECTION 2: Hazards Identification

2.1. Classification:

Carcinogenicity Cat. 1A; H350 (inhalation)

Specific Target Organ Toxicity, Repeated Exposure Cat. 1; H372 (inhalation)

2.2. Label elements:



GHS08

Danger

- May cause cancer (Inhalation).
- May cause damage to organs (lung, kidney, liver, thyroid gland, and immune system) through prolonged and repeated exposure (oral and inhalation).

Prevention

- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Do not breathe dust or spray.
- Wash hands and exposed skin thoroughly after handling.
- Do not eat, drink, or smoke when using this product.
- Wear protective gloves and safety glasses or goggles.

Response

- If exposed or concerned, get medical attention.

Storage

- Store locked-up.

Disposal

- Dispose of contents and containers to comply with local, regional, national, and international regulations.



Ready-Mix Joint Compounds

Safety Data Sheet

Revision date: 05/31/2017

Version: 2.0

2.3. Other hazards

Exposures to nuisance particles or dusts may cause irritation to the eyes and upper respiratory tract.

SECTION 3: Composition / Information on Ingredients

<u>Chemical Name</u>	<u>CAS No.</u>	<u>Wt. %</u>
Calcium carbonate	1317-65-3	36
Perlite	93763-70-3	12
Mica	12001-26-2	8
Kaolin clay	1332-58-7	6
Talc	14807-96-6	4
Attapulgate clay	12174-11-7	3
Total Crystalline silica – <i>Not added directly but present as an impurity in ingredients listed above.</i>	14808-60-7	0.2 – 0.6

SECTION 4: First Aid Measures

4.1. Description of first aid measures:

Inhalation: If breathing is difficult, remove affected person to fresh air and keep at rest in a position comfortable for breathing. If exposed or concerned: Get medical attention.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If irritation persists get medical attention.

Skin Contact: If on skin, wash with plenty of soap and water. If skin irritation or rash occurs get medical advice. Take off contaminated clothing and wash it before reuse.

Ingestion: If swallowed, call a POISON CENTER or doctor. Rinse mouth. Never give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing.

4.2. Most important symptoms / effects acute and delayed:

Inhalation: Exposures to airborne dust may cause irritation to the upper respiratory tract; symptoms of exposure may include sneezing, coughing and sore throat.

Prolonged or repeated exposure to fine airborne crystalline silica dust may cause damage to lung tissue, a disease called silicosis. Symptoms of silicosis include cough, shortness of breath upon exertion and chest tightness. The symptoms of silicosis develop following long-term exposures to airborne dusts containing silica. May cause lung cancer by inhalation.

Eye Contact: Dust particles may cause mechanical irritation.

Skin Contact: Dust particles may cause mechanical irritation.

Ingestion: If swallowed, may cause stomach discomfort.

4.3. Indication of any immediate medical attention and special treatment needed:

Not applicable

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing media:

Use water and other extinguishing media appropriate to the surrounding fire conditions.

Unsuitable extinguishing media: None known.

5.2. Special hazards arising from the product:

Product is not flammable and does not support combustion.

5.3. Special protective equipment and precautions for fire-fighters:

As for any fire, fire-fighters protective clothing and positive pressure SCBA may be necessary.

SECTION 6: Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures:

Wear adequate personal protective equipment, including an appropriate respirator as indicated in Section 8. Isolate spill area, preventing entry



Ready-Mix Joint Compounds

Safety Data Sheet

Revision date: 05/31/2017

Version: 2.0

by unauthorized persons. Ventilate the spill area if airborne dust is present.

6.2. Environmental precautions:

Prevent releases into the environment.

6.3. Methods and material for containment and cleaning-up:

Use methods that avoid raising dust in the air. Scoop or shovel spilled material or vacuum dust with equipment fitted with a HEPA filter and place in a closed, labelled waste container. Small spills may be picked up with a damp cloth or mop.

SECTION 7: Handling and Storage

7.1. Precautions for safe handling:

- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Do not breathe airborne dusts or spray.
- Wear eye protection and gloves.
- In workplaces where occupational exposure limits are exceeded, wear appropriate respiratory protection. (See Section 8).
- Read the label and follow the directions for use.
- Wash hands and exposed skin thoroughly after handling.
- Do not eat, drink or smoke in the workplace where this product is handled.

7.2. Conditions for safe storage, including any incompatibilities:

- Store in dry conditions and protected from weather.
- Keep containers closed when not in use.
- Keep out of reach of children.

SECTION 8: Exposure Controls / Personal Protection

8.1. Control parameters:

Occupational Exposure Limits: Consult local authorities for acceptable exposure limits.

Ingredient	ACGIH® TLV®	U.S. OSHA PEL	RSST VEMP (CNESST – Quebec)
Calcium carbonate	Not established	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)	10 mg/m ³ (total dust)
Perlite	Not established	Not established	15 mg/m ³ (total dust) 5 mg/m ³ (respirable)
Mica	3 mg/m ³ (respirable)	3 mg/m ³ (respirable fraction)	3 mg/m ³ (respirable)
Kaolin clay	2 mg/m ³ (respirable)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)	5 mg/m ³ (respirable)
Talc	2 mg/m ³ (respirable)	2 mg/m ³ (respirable)	3 mg/m ³ (respirable)
Attapulgite clay	10 mg/m ³ (inhalable) 3 mg/m ³ (respirable) PNOS	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction) Table Z-3 Mineral dust	1 fibre/cm ³
Crystalline silica, quartz	0.025 mg/m ³ (respirable)	Quartz (total dust): 30 mg/m ³ / (%SiO ₂ +2) Quartz (respirable): 0.05 mg/m ³ / (%SiO ₂ +2) Table Z-3	0.1 mg/m ³ (respirable)

8.2. Exposure controls:

Engineering Controls: General ventilation is adequate for application of product in its original form. If airborne particulates are generated, monitor concentrations in air and provide local exhaust ventilation when any exposure guideline is exceeded. Dust collection systems must be designed and maintained to prevent the accumulation and recirculation of respirable silica into the workplace air.

If engineering controls and work practices are not effective in controlling exposure to this material or if adverse health symptoms are experienced, wear suitable personal protection equipment including approved respiratory protection.

Eye/Face Protection: Wear safety glasses or goggles.

Skin Protection: Wear protective gloves; e.g. nitrile gloves. Where workplace conditions generate dust, wear protective clothing; e.g. coveralls. Launder contaminated clothing before re-wearing, or discard.



Ready-Mix Joint Compounds

Safety Data Sheet

Revision date: 05/31/2017

Version: 2.0

Respiratory Protection: When dust or spray concentrations in air exceed the occupational exposure guideline, wear an approved air-purifying respirator.

NIOSH recommendations for Crystalline silica (respirable dust); concentrations in air:

Up to 0.5 mg/m³: particulate respirator equipped with an N95, R95, or P95 filter (including N95, R95, and P95 filtering facepieces) except quarter-mask respirators. The following filters may also be used: N99, R99, P99, N100, R100, P100.

Up to 1.25 mg/m³: Powered air-purifying respirator with high-efficiency particulate filter; or SAR operated in a continuous-flow mode.

Up to 2.5 mg/m³: air-purifying, full-facepiece respirator with an N100, R100, or P100 filter.

Up to 25 mg/m³ Positive pressure SAR.

A respiratory protection program that meets the regulatory requirement, such as OSHA's 29 CFR 1910.134, ANSI Z88.2 or Canadian Standards Association (CSA) Standard Z94.4, must be followed whenever workplace conditions warrant a respirator's use.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties:

Appearance	: Paste, semi-solid. Off white
Odour	: Faint
Odour threshold	: Not available
pH	: 7 – 10 (aqueous slurry)
Melting point / Freezing point	: Approximately 0 °C
Initial boiling point and boiling range	: Approximately 100 °C
Flash point	: Not applicable
Flammability	: Not flammable or combustible
Auto-ignition temperature	: Not available
Upper / lower flammability or explosive limits	: Not applicable
Evaporation rate	: Not applicable
Vapor pressure	: Not applicable
Vapor density	: Not applicable
Relative density	: 0.9 – 2.0 (water = 1)
Solubility (ies)	: Low solubility in water
Partition coefficient (n-octanol / water)	: Not available
Decomposition temperature	: Not available
Viscosity	: 100-800 Brabender Units
VOC content	: < 3 g/L

SECTION 10: Stability and Reactivity

10.1. Reactivity:

Not reactive under normal conditions of use.

10.2. Chemical stability:

Normally stable.

10.3. Possibility of hazardous reactions:

None known.

10.4. Conditions to avoid:

Avoid accumulations of dust.

10.5. Incompatible materials:

Strong acids. Strong oxidizing agents.

10.6. Hazardous decomposition products:

Calcium oxide, corrosive fumes, may form if product is exposed to extreme heat 825 °C (1517 °F).



Ready-Mix Joint Compounds

Safety Data Sheet

Revision date: 05/31/2017

Version: 2.0

SECTION 11: Toxicological Information

11.1. Information on toxicological effects:

Likely routes of exposure

Inhalation; Skin contact; Eye contact.

Acute toxicity

Inhalation: Data not available. None of the natural mineral component substances are toxic or harmful by inhalation.

Ingestion: Data not available. None of the natural mineral component substances are toxic or harmful if swallowed.

Skin: Data not available. Component natural mineral component substances are not known to be absorbed through the skin.

Acute toxicity data:

Acute toxicity estimate (oral) of the mixture: >7000 mg/kg (rat) based on data for the component substances.

Low dermal and inhalation acute toxicity based on evidence from animal tests.

<u>Ingredient</u>	<u>LD₅₀ Oral (mg/kg)</u>	<u>LD₅₀ Dermal (mg/kg)</u>	<u>LC₅₀ Inhalation (ppm, 4 hrs.)</u>
Calcium carbonate	6450 (rat)	Not available	Not available
Perlite	>13000 mg/kg (mouse)	Not available	Not available

Skin corrosion / irritation

Data not available. May cause skin dryness and abrasive irritation in contact with the skin.

Serious eye damage / irritation

Data not available. Particulates in the eye may cause irritation by mechanical action.

STOT (Specific Target Organ Toxicity) – Single exposure

Data not available

STOT (Specific Target Organ Toxicity) – Repeated exposure

Repeated exposures to particles containing crystalline silica can cause lung disease (silicosis).

Silicosis is characterized by lung lesions. Symptoms of silicosis include shortness of breath and cough, decreased lung function and weakness.

There is limited evidence of kidney, liver, thyroid gland, and immune system disease in humans following occupational exposures to crystalline silica.

Aspiration hazard

Does not meet criteria for classification for aspiration toxicity.

Sensitization – respiratory and/or skin

Not known to be a respiratory or skin sensitizer.

Carcinogenicity

Crystalline Silica:

IARC Crystalline Silica in the form of quartz or cristobalite from occupational sources should be classified as carcinogenic to humans (Group 1).

ACGIH® in the form of quartz or cristobalite as A2: Suspected human carcinogen.

Crystalline silica, respirable size, is listed in the Report on Carcinogens by NTP (National Toxicology Program) as known to be a human carcinogen.

Reproductive toxicity

Data no available

Germ cell mutagenicity

Data not available

Interactive effects

Tobacco smoking in combination with inhalable silica exposures may have higher risk of developing lung disease.

Persons who develop silicosis have a higher risk of contracting tuberculosis if exposed to the tuberculosis bacteria.



Ready-Mix Joint Compounds

Safety Data Sheet

Revision date: 05/31/2017

Version: 2.0

SECTION 12: Ecological Information

12.1. Toxicity:

Ecotoxicity data are not available. Composed of natural source minerals.

12.2. Persistence and degradability:

Not available

12.3. Bioaccumulative potential:

Not available

12.4. Mobility in soil:

Not available

12.5. Other adverse effects:

Not available

SECTION 13: Disposal Considerations

13.1. Disposal methods:

Dispose of as an inert solid.

Do NOT discharge into any drains or sewers.

The required hazard evaluation of the waste and compliance with the applicable hazardous waste laws are the responsibility of the user.

Dispose of contents/container in accordance with local, regional, national and international regulations.

SECTION 14: Transport Information

14.1. UN number:

Not regulated by international transport regulations (IMDG, UN Model Regulations).

14.2. UN proper shipping name:

Not applicable

14.3. Transport hazard class(es):

Not applicable

14.4. Packaging group:

Not applicable

14.5. Environmental hazards:

Not available

14.6. Special precautions for user:

Not available

14.7. U.S. Hazardous Materials Regulation (DOT 49CFR):

Not regulated

14.8. Canada Transportation of Dangerous Goods (TDG) Regulations:

Not regulated



Ready-Mix Joint Compounds

Safety Data Sheet

Revision date: 05/31/2017

Version: 2.0

SECTION 15: Regulatory Information

15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture:

USA

TSCA Status: Substances are listed on the TSCA inventory or are exempt.

California Prop 65: This product may contain a substance known to the State of California to cause cancer [Crystalline silica – airborne particles of respirable size. Palygorskite (Attapulgite) fibers >5 mm in length].

Canada

WHMIS Classification: WHMIS 2015: D2A Untested mixture containing Crystalline silica (IARC Group 1).

NSNR Status: Component substances are listed on the DSL or are exempt.

SECTION 16: Other Information

References and sources for data:

CCOHS, Cheminfo
RTECS, Registry of Toxic Effects of Chemical Substances
NIOSH, Pocket Guide to Chemical Hazards

Methods for classification of mixtures:

USA: Haz Com Standard 29 CFR 1910.1200 (2012)
Canada: Controlled Products Regulations
UNECE, Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Legend to abbreviations:

ACGIH – American Conference of Governmental Industrial Hygienists
CNESST – Commission des normes, de l'équité, de la santé et de la sécurité du travail
GHS- Globally Harmonized System for Classification and Labeling.
IARC - The International Agency for Research on Cancer
NIOSH – National Institute for Occupational Safety and Health
NTP – National Toxicology Program
OEL– Occupational exposure limit
OSHA - Occupational Safety and Health Administration
RSST – Règlement sur la santé et la sécurité du travail
TWA – Time weighted average
TLV - Threshold Limit Value
VEMP – Valeur d'exposition moyenne pondérée
WHMIS – Workplace Hazardous Materials Information System.

Additional information:

This information is furnished without warranty, expressed, or implied, except that it is accurate to the best knowledge of Hamilton Drywall Products. The data on this sheet relates only to the specific material designated herein. Hamilton Drywall Products assumes no legal responsibility for the use or reliance on this data.