



CONSTRUCTION TAPE

TYPAR Construction Tape is a polypropylene sheathing tape coated with an aggressive acrylic pressure sensitive adhesive (PSA) designed for use as a closure system and vapor seal on all exterior sheathing materials.



Engineered for commercial and residential applications

Features & Benefits

- ✓ High performance sheathing tape installs
- ✓ Performs well over a wide temperature range
- ✓ Excellent vapor barrier tape
- ✓ Great adhesion at low temperatures
- ✓ Excellent tensile strength

TEST	TYPICAL VALUE* (English)	TYPICAL VALUE* (Metric)	TEST METHOD
Thickness	3.0 mils	0.08 mm	PSTC-133
Peel Adhesion Δ			
-to stainless steel	45 oz/in	12.5 N/25 mm	PSTC-101
-to polyethylene	16 oz/in	4.5 N/25 mm	PSTC-101
Shear Adhesion	>24 hrs @ 2.2 psi	>24 hrs @15.2 kPa	PSTC-107
Tensile Strength	20 lb/in	90.4 N/25 mm	PSTC-131
Elongation	130%	130%	PSTC-131
WVTR		0.061 perms	ASTM E96
Service Temperature	0 to 185 OF	-17.8 to 85 OC	

Δ -20 minute dwell.

*Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; 3M recommends that the purchaser test for fitness for use in all applications.

Roll Dimensions:

Size: 60 mm x 55 m

Rolls/Case: 20



CCMC Approved 1585CW-P2

a pgi brand

70 Old Hickory Blvd., Old Hickory, TN 37138 USA
+1 (615) 847 7216
TYPAR.com

The information contained herein is to the best of our knowledge accurate and reliable and is provided for the user's assessment and verification. However, since the circumstances and conditions under which such information and the products discussed can be used may vary and are beyond our control, we make no warranty, expressed or implied, of a merchantability, fitness or otherwise, or of the results to be obtained, or against patent infringement, and we disclaim all liability from any resulting damage or loss.

TYPAR® is a registered trademark of Polymer Group Inc. © 2014

Literature No: CONSTRUCTIONTAPESELLSHEET



**Peace of mind with
TYPAR Weather
Protection System**